

Optimal Air Distribution & Light Commercial Comfort Control



Sizes: 36 / 48

KEY FEATURES

Built-in Condensate Lift Pump

The cassette is supplied with a condensate lift pump that is capable of lifting the water 29.5 in. (750 mm.) above the top of the unit.

360° Air Flow Panel

With the 360° air flow panel, air is distributed to every corner of the room.

CONTROLS

Wireless Remote Controller included with indoor unit

Optional Wired Remote Controller
KSACN0101AAA (Timer Function)

Optional Wired Remote Controller
KSACN0501AAA (7-Day Programmable)

INDOOR FEATURES

- Available in 208/230V
- Up to 17.5 SEER and 11.0 HSPF when paired with 38MBR outdoor unit
- Modes: Cool, Heat, Dry, Fan, Auto
- Auto-restart function
- Louver control (fixed or swing)
- Three fan speeds
- Outside air intake
- Built-in condensate lift pump
- Follow Me (senses temperature at the handheld remote)
- Heating Setback (46° F Heating Mode)
- Quiet indoor operation, as low as 49 dB(A)
- Aluminum Golden Hydrophilic pre-coated fins
- Grille/ceiling panel 3' x 3' P/N 40MBCQ02XXX3



Wireless Remote Controller



Wired Remote Controller
(7-Day Programmable)
KSACN0501AAA

COMPATIBLE WITH:

- 38MBR Outdoor Unit Single Zone

ACCESSORIES

Wi-Fi® Kit KSAIF0401AAA




NOTE: Grille is required; sold separately.

DUCTLESS SYSTEMS

EXCEL SERIES

40MBCQ CASSETTE



SPECIFICATIONS:

40MBCQ Cassette			
Heat Pump System			
Size		36	48
Indoor Model		40MBCQ36---3	40MBCQ48---3
Electrical			
Voltage-Phase-Cycle		V-Ph-Hz	208/230-1-60
Power Supply		Indoor unit powered from outdoor unit	
MCA		A.	0.8
Operating Range			
Cooling Indoor DB Min - Max		° F (° C)	63~90 (17~32)
Heating Indoor DB Min - Max		° F (° C)	32~86 (0~30)
Piping			
Pipe Connection Size - Liquid		in (mm)	3/8 (9.52)
Pipe Connection Size - Suction		in (mm)	5/8 (16)
Indoor			
Body Unit Width		in (mm)	33.07 (840)
Body Unit Height		in (mm)	9.65 (245)
Body Unit Depth		in (mm)	33.07 (840)
Body Net Weight		lbs (kg)	58.2 (26.4)
Panel Unit Width		in (mm)	37.4 (950)
Panel Unit Height		in (mm)	2.17 (55)
Panel Unit Depth		in (mm)	37.4 (950)
Panel Net Weight		lbs (kg)	11.02 (5)
Number of Fan Speeds			3
Airflow (lowest to highest)		CFM	809/958/1095
Sound Pressure (lowest to highest)		dB(A)	49/52/55
Air Throw Data		ft (m)	30 (9)
Moisture Removal		Pint/h (L/h)	8.53 (4.04)
Field Drain Pipe Size O.D.		in (mm)	1 (25.4)

COMPATIBILITY:

Indoor Unit	40MBCQ36---3	40MBCQ48---3
Outdoor Unit Single Zone*	38MBRQ36A--3	38MBRQ48A--3

*Performance may vary based on the compatible outdoor units. See respective pages for performance data.

Manufacturer reserves the right to discontinue, or change at any time, specification or designs without notice or incurring obligations.