



Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	Field installed kit available
Number of Poles	3
Current Rating	200 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 3R galvanized steel
Motor power hp	15 Hp at 240 V AC 50/60 Hz for 1 phase motors 60 Hp at 240 V AC 50/60 Hz for 3 phase motors 50 Hp at 480 V AC 50/60 Hz for 1 phase motors 125 Hp at 480 V AC 50/60 Hz for 3 phase motors 50 Hp at 600 V AC 50/60 Hz for 1 phase motors 150 Hp at 600 V AC 50/60 Hz for 3 phase motors 40 Hp at 250 V DC 50 hp at 600 V DC

Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire
Wire Size	AWG 6...250 kcmil copper or aluminium
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.2 in ² (13.3...127 mm ²) (AWG 6...250 kcmil)
Depth	8.506 in (216.052 mm)
Width	17.016 in (432.206 mm)
Height	28.94 in (735.08 mm)
Net Weight	44.004 lb(US) (19.96 kg)
Grounding Kit	Field installed kit available
Service Entrance	Suitable service entrance for USA Suitable service entrance for Mexico

Environment

Certifications	UL listed file E2875
----------------	----------------------

Ordering and shipping details

Category	US10DE100009
Discount Schedule	ODE1
GTIN	3606485894942
Returnability	Yes
Country of origin	US

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.3750 in (49.2125 cm)
Package 1 Width	8.3125 in (21.1137 cm)
Package 1 Length	30.0000000000 in (76.2 cm)
Package 1 Weight	54.5 lb(US) (24.7 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations