

818 Large Diameter Series

APOLLOXPRESS® Press End **Copper Reducer** FTGxC (3" x 2 ½" through 4" x 3")



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	







DESCRIPTION

The APOLLOXPRESS® 818 Large Diameter Press Reducer features a Lead-Free dezincification resistant copper body, a patented stainless-steel solid cross-section Grab Ring, a Nylon Separation Ring and an EPDM O-Ring. Our Large Diameter APOLLOXPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly Made In The USA.

FEATURES

- Lead-Free Construction
- Leak-Before-Press Technology
- Visual element, Break Away Band (Pat. Pending)
- Compatible with XL-C™ Pressing Tools
- Approved for underground installation (per local installation code)
- Use with hard/soft ASTM B88 K, L & M Copper Tube
- Made in USA
- cUPC® Compliant
- ARRA Compliant

PERFORMANCE RATING

- Maximum Pressure: 200 psi
- Temperature Range: o°F to 250°F depending on application. Hot Water up to 250°F, Chilled Water down to 33°F

APPROVALS

- NSF/ANSI NSF 61 ~ Water Quality
- NSF/ANSI NSF-372 ~ Lead Free (LF)
- IAPMO File Listings: 4861, 6174 & N-4951

APOLLOXPRESS

- Large Diameter Sizes 3" x 2 ½", 4" x 2 ½", 4" x 3"
- Model 818, Fitting Reducer FTG x C.


STANDARD MATERIALS

Part Name	Material			
Body	UNS C12200 Copper			
Grab Ring	304 / 306 Stainless Steel			
Spacer Ring	Nylon 66			
O-Ring	EPDM			
Lubrication	Silicone, ANSI/NSF-61 Listed			

DIMENSIONS

		Dimension (in.)								
Item No.	Description	Α	В	C*	D**	E***	Height	Width	Depth	Weight
10057500	818 3x2½ FTGxC	5.09	3.16	1.90	3.19	2.51	3.16	5.09	3.16	1.60
10057503	818 4x2½ FTGxC	6.02	4.13	1.90	4.12	2.67	4.13	6.02	4.13	2.55
10057506	818 4x3 FTGxC	5.90	4.13	2.10	3.81	2.65	4.13	5.90	4.13	2.77

^{*} Tolerance +/- .02"



Elkhart Products Corporation

1255 Oak Street, Elkhart, IN 46514 www.elkhartproducts.com | (574) 264-3181

This specification is provided for reference only. Elkhart Products Corporation reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Elkhart products previously or subsequently sold.



^{**} Tolerance +.15 / -.03

^{***} Tolerance +.12 / -.00