

FLEX-LOC™ PUSH-ON

Flex-Loc™ is a highly oil-resistant push-on hose with a 250 psi working pressure, designed for safe and reliable performance in the most demanding and harsh working conditions. It allows push-on fittings to be inserted into place easily and quickly without the need for special crimping tools are required. Its tube and cover make it effective for industrial, warehouse and other applications where a convenient push-on hose fitting could be used.

Not recommended for unleaded gasoline.



RESISTANCE 
BRANDING Size WP – Flex-Loc – Made In USA

Cover Color: Black, Blue, Gray, Red, Green or Yellow
Oil Resistance: High
Construction:
Tube: Nitrile, RMA Class A
Cover: Nitrile/PVC RMA Class A
Reinforcement: Spiral polyester
Temperature Range: -20°F to +180°F
 -29°C to +82°C
Packaging: Reels 500 - 700 ft. or 250 ft.

Product Number (500 - 700 ft. reels)	Product Number (250 ft. reels)	Nominal I.D. (inches) (mm)		Nominal O.D. (inches) (mm)		Reinforcement Spirals	Working Pressure (psi) (Mpa)		Min. Bend Radius (inches) (mm)		Weight (lb/ft) (Kg/m)	
Black												
00338404300	00338404398	1/4	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338406300	00338406398	3/8	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338408300	00338408398	1/2	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24
00338410300	00338410398	5/8	15.88	0.91	23.02	2	250	1.72	3.75	95.25	0.22	0.33
00338412300	00338412398	3/4	19.05	1.03	26.19	2	250	1.72	4.50	114.30	0.25	0.37
Blue												
00338504300	00338504398▲	1/4	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338506300	00338506398	3/8	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338508300	00338508398▲	1/2	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24
Gray												
00338604300	00338604398▲	1/4	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338606300	00338606398▲	3/8	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338608300	00338608398▲	1/2	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24
Red												
00338704300	00338704398▲	1/4	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338706300	00338706398▲	3/8	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338708300	00338708398▲	1/2	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24
Green												
00338804300▲	00338804398▲	1/4	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338806300	00338806398▲	3/8	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338808300▲	00338808398▲	1/2	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24
Yellow												
00338904300▲	00338904398▲	1/4	6.35	0.50	12.70	2	250	1.72	1.50	38.10	0.09	0.13
00338906300▲	00338906398▲	3/8	9.53	0.63	15.88	2	250	1.72	2.25	57.15	0.12	0.18
00338908300▲	00338908398▲	1/2	12.70	0.75	19.05	2	250	1.72	3.00	76.20	0.16	0.24

▲ = Make To Order (MTO)

AIR/MULTIPURPOSE