

PS SS – Clamping Nut with Short Spring



Size	Threads	Wt./100 pcs	Available in [DF]
#8-32	32	7.0	--
#10-24	24	7.0	--
#10-32	32	7.0	--
1/4"	20	6.9	X
5/16"	18	6.7	--
3/8"	16	9.6	X
1/2"	13*	8.8	X
5/8"	11*	11.5	--
3/4"	10*	10.0	--

Use With: PS 400, PS 500, PS 520, and PS 560 channel.

*PS SS 1/2" and PS SS 5/8" nuts have 3/8" body thickness.

MATERIAL:

Channel clamping nuts meet ASTM A576 GR1015M, and are case hardened.

STANDARD FINISH:

All fasteners have an electro-galvanized finish.

SCREW THREADS DATA:

All Power-Strut nuts and bolts are manufactured to meet the Unified Screw Threads standard, ANSI B1.1, Coarse Series UNC, class 2.

POWER-STRUT® DEFENDER™ FINISH [DF]:

Power-Strut Defender is a combination of two proprietary material coatings conforming to ASTM standards A1046 and A1059. It features unique self-healing properties.



**POWER-STRUT®
DEFENDER™**

Project: _____

Approval Stamp:

Architect / Engineer: _____

Date: _____ Phone: _____

Contractor: _____

Address: _____

Notes 1: _____

Notes 2: _____
