Red Devil Celulon And Acrylic Caulk

Celulon™ plumbing and HVAC adhesive sealant is sometimes preferred over silicone. This easy to apply adhesive sealant adheres to all substances, is paintable, cleans up with water and has no offensive odor. Used to seal A/C ducts and lines. Application temp: 40 ° to 90°F. Service temp: -25° to 200°F.





MARS NO.	DESCRIPTION			MARS PACK	CASE QTY.
93256	Celulon HVAC sealant	clear	10.1 oz.	12	12
93257	Celulon HVAC sealant	white	10.1 oz.	12	12
93258	35 yr. acrylic caulk	gray	10.1 oz.	12	12

Red Devil Butyl Sealants

Red Devil's butyl sealant is a high performance rubber-like sealant that is ideal for tough outdoor jobs and below grade applications. (marine usage above waterline) It can be used wherever watertight seal is required. This paintable sealant provides excellent adhesion to most building surfaces including aluminum, stone, wood, brick, fiberglass, plastic, metal, etc. This sealant is ideal for use on window/door frames, aluminum gutters, chimney roofs, concrete foundations etc. Sealant remains



Red Devil (*)

rubbery and flexible from 0°F to 225°F after full cure.

MARS NO.	DESCRIPTION		MARS PACK	CASE QTY.	
93290	Butyl sealant	white	10.1 oz.	12	12
93291	Butyl sealant	aluminum gray	10.1 oz.	12	12

Red Devil Specialty Products

Red Devil's blacktop & roof repair is water resistant and stays flexible. This butyl rubber asphalt sealant adheres to cinder block, wood asphalt, concrete, brick and metal. Use on blacktop driveway cracks, chimney flashings, shingles & skylights. Apply at temperatures between 10°F & 100°F. Full cure in 72 hours Red Devil speed demon latex caulk is a general purpose caulk that applies easily, dries quickly is paintable and won't stain or bleed. Red Devil's Kitchen & Bath caulk provides a long lasting water-tight seal around tubs, showers & sinks. This odorless and mildew resistant caulk is paintable & wont stain or bleed. The acrylic based caulk features a quick protection





MARS NO.	DESCRIPTION			MARS PACK	CASE QTY.
93244	Blacktop & roof repair	black	10.1 oz.	12	12
93265	Speed demon latex caulk	white	10.1 oz.	12	12
93248	Kitchen & bath caulk	white	5.5 oz.	12	12

Expanding Foam Sealing Products

formula (QPF) which forms a protective outer covering in

seconds allowing a bath or shower

within 3-4 hours use of application.

MARS foam sealant is a multipurpose expanding polyurethane foam sealant, designed for the professional contractor. Excellent for HVAC projects and wall/floor penetrations. It is ideal for sealing around air conditioners, vents, ducts, electrical and plumbing penetrations. The Handi-Foam, MARS #93243, is a two component polyurethane foam to seal, bond, retrofit, insulate and dampen sound. Excellent for use in the HVAC, plumbing, roofing, cold storage, transportation and building maintenance applications, Expands and cures within seconds. Conforms to any shape. Each kit contains 2 cans

(.88 lbs. ea.) of polyurethane



expanding foam, two spray nozzles with 24" hoses and 1" clamp. Covers one cubic foot (12 board feet).

MARS NO.	DESCRIPTION	MARS PACK	CASE QTY.
93268	Foam sealant 12 oz.	12	12
93267	Foam sealant 24 oz.	12	12
93243	Handi-Foam	1	12

