



MARKERS, TEMPERATURE INDICATORS, INDUSTRIAL COATINGS AND CHEMICALS FOR WELDERS LA-CO Industries creates specialized products that are RIGHT FOR THE JOB[™], and will help professional welders get the job done right. From general marking tools to markers made especially for the unique needs of welders, and from temperature indicators to industrial coatings and chemicals, you'll find the products that will always perform to your professional standards.

MARKAL

No other marker manufacturer has the quality, the precision, and the range of products for welders and general industry as MARKAL. Made in the USA, and manufactured to deliver outstanding results, MARKAL is the welding industry's marking standard.

TEMPIL

From Tempilstik[®] to Bloxide[®], Tempil is known worldwide as the performance leader in temperature indicating, monitoring and coatings. Welders depend on Tempil's precision and technical capabilities, making each Tempil product exactly **RIGHT FOR THE JOB**[™]

LA-CO

Providing quality products for the plumbing, pipefitting, HVAC, and maintenance operations professional, LA-CO is a global leader in chemicals for a wide range of applications and solutions.



Valve Action[®] Paint Marker Liquid paint marker for general marking

Fast-drying liquid paint marker that provides longlasting, wear- and weather-resistant marking that's safe for almost any surface. Known as the most versatile liquid paint marker in the world, our xylene-free paint reduces health risks and is available in 18 bold and fluorescent colors for accurate mark identification.

FEATURES & BENEFITS:

- Fast-drying, permanent paint for immediate handling reduces work downtime
- Dura-Nib medium bullet tip resists wear to provide long marking life
- Marking range: -50°F to 150°F (-46°C to 66°C)

| | 1993 B. 🛯 | 100 | TAR A DISTORT OF THE OWNER OWNER OF THE OWNER OWNER OF THE OWNER |
|---|-----------|-----|--|
| e | 96809 | | Brown* |
| | 96817 | | Purple* |
| | 96820 | | White* |
| | 96821 | | Yellow* |
| | 96822 | | Red* |
| | 96823 | | Black* |
| | 96824 | | Orange* |
| | 96825 | | Black* Orange* Blue* |
| | 96826 | | Green* |
| | 96827 | | Gold* |
| | 96828 | | Light Green* |
| | 96830 | | Pink* |
| | 96832 | | Aluminum* |
| | 96835 | | Light Blue* |
| | 97050 | | Fluorescent Yellow |
| | 97051 | | Fluorescent Green |
| | 97052 | | Fluorescent Orange |
| | 97053 | | Fluorescent Pink |
| | | | |





PRO-LINE[®] HP Liquid paint marker for oily surface marking

Developed for superior marking performance on oily and greasy surfaces. The high performance paint penetrates through oils and greases to dry quickly and leave a bold, permanent mark that is wear-, Markal HP Marka weather-, and fade-resistant.

FEATURES/BENEFITS:

- Xylene-free paint reduces user health risks and eliminates California Proposition 65, EPA HAPS and SARA 313 concerns in the U.S.A.
- Easy-to-grip clip-cap allows for convenient pocket storage
- Marking range: -50°F to 150°F (-46°C to 66°C)

| 96960 | White* |
|-------|-------------------|
| 96961 | Yellow* |
| 96962 | Red* |
| 96963 | Black* |
| 96964 | Orange* |
| 96965 | Blue [*] |
| 96966 | Green |
| 96967 | Silver* |
| 96970 | Light Green |
| 96971 | Light Blue* |
| 96972 | Gold |
| 96973 | Pink* |
| 96974 | Purple |
| 96975 | Brown* |
| | |

B° Paintstik° Multi-purpose permanent solid paint crayon

As Markal's most versatile and economic marker, the original B Paintstik solid paint marker combines the durability of paint in the convenience of a crayon. The real paint formula has superior marking performance on oily, icy, wet, dry or cold surfaces and is weatherand UV-resistant. This Paintstik works on rough, rusty, smooth, or dirty surfaces.

PRO-LINE[®] **XT** Liquid paint marker for rough surfaces and extreme durability

Engineered for the ultimate marking performance on rough, rusty, and dirty surfaces that utilizes an enamel resin to provide enhanced wear-, weather-, and chemicalresistance. The fast-drying paint formula binds quickly to materials to leave a bold, highly-visible mark.

B Markal XT Markan Marganese

FEATURES/BENEFITS:

- Available in 14 bold, fast-drying colors for immediate handling and reduced downtime
- Xylene-free paint reduces user health risks and eliminates California Proposition 65, EPS HAPS, and SARA 313 concerns in the U.S.A.
- Marking range: -50°F to 150°F (-46°C to 66°C)

| 97250 | White* |
|-------|--------------|
| 97251 | Yellow* |
| 97252 | Red* |
| 97253 | Black* |
| 97254 | Blue* |
| 97255 | Green* |
| 97256 | Orange* |
| 97257 | Silver* |
| 97258 | Light Green* |
| 97259 | Light Blue* |
| 97260 | Gold |
| 97261 | Pink* |
| 97262 | Purple |
| 97263 | Brown* |



FEATURES/BENEFITS:

- Real paint for long-lasting, highly visible marks
- Superior marking on rough, rusty, or dirty surfaces sharpening or priming, increasing productivity
- Weather- and UV-resistant for long-lasting marks

| 80220 | White* | 80227 | Pink |
|-------|--------|-------|--------------------|
| 80221 | Yellow | 80228 | Purple |
| 80222 | Red | 80229 | Brown |
| 80223 | Black | 80230 | Gray |
| 80224 | Orange | 80231 | Gold |
| 80225 | Blue | 80232 | Aluminum |
| 80226 | Green | 80233 | Fluorescent Yellow |

Quik Stik[®] Fast-drying solid paint in twist-up holder

Quik Stik is a smooth-marking solid paint crayon that dries quickly to leave a bold, permanent mark on most surfaces. The durable plastic twist-up holder prevents breakage. Keep hands, clothing, and toolboxes clean with the industry's largest twist-up solid paint marker.

FEATURES & BENEFITS:

- Fast-drying, vibrant paint marks dry in 5 to 7 minutes
- Marks on virtually any surface: wet, smooth, rough, or hot

Markal Autom

- Weather- and UV-resistant paint for long-lasting mark
- Marking range: 0°F to 392°F (-18°C to 200°C)

61049 📕 Red 61050 Black 61051 White 61053 📃 Yellow 61069 📃 Green 61070 Blue 61071 Orange 61073 Purple

Quik Stik[®] Mini Fast-drying solid paint in twist-up holder

The Quik Stik Mini is a compact solid paint marker in a convenient twist-up, plastic holder that is ideal for finer line marking on smooth or rough surfaces. This smaller version of the Markal[®] Quik Stik conveniently stores in a pocket or tool belt and easily advances with the turn of a knob, allowing for full use of the marker. The high-performance paint dries quickly to leave bold, permanent marks on most surfaces.

FEATURES & BENEFITS:

- Fast-drying, vibrant paint marks dry in 5 to 7 minutes
- Marks on virtually any surface: wet, smooth, rough, or hot
- Weather- and UV-resistant paint for long-lasting mark
- Marking range: 0°F to 392°F (-18°C to 200°C)

| 61126 | White |
|-------|--------|
| 61127 | Yellow |
| 61128 | Red |
| 61129 | Black |

Silver Streak® & Red Riter® Welders Pencils Welders pencils for metal layout and fabrication

Markal Silver-Streak and Red-Riter welders pencils make torch-resistant marks that will not burn or rub off like soapstone. Ideal for fine line marking during metal layout and fabrication, these highly visible marks illuminate

When cutting or welding.

Model[®] Red-Riter[®] Welders Pencil

FEATURES/BENEFITS:

Durable marks will not scratch or abrade metal surfaces

a/* Red-Riter* Welders Pencil **

- Available in two highly visible colors: red for aluminum or other bright metals, silver for darker surfaces
- High-strength, hex-shaped pencil reduces barrel roll



Red Riter[®] **Metal Marker** Layout and fabrication marker for aluminum, bright metals

Ideal for use on aluminum and stainless steel, Red-Riter metal markers deliver high visibility, resistant-to-torchflame marks. The red lead is more visible through a welder's filter plate. Unlike soapstone, durable marks will not rub, burn or blow off during metal layout and fabrication work.

FEATURES/BENEFITS:

- Highly visible marks illuminate when cutting or welding
- Marks on oily, wet or rusty metals, and will not scratch or abrade surfaces
- Rugged metal holder prevents stick breakage and includes handy pocket clip for easy storage when not in use

96005 Flat 96019 Flat Refill Pack

Silver Streak[®] **Metal Marker** For welding, metal layout and fabrication

Markal Silver-Streak metal markers are ideal when highlyvisible, torch-resistant marks are required during metal layout and fabrication work. The unique reflective lead is more visible through a welder's filter plate and will not rub, burn or blow off like soapstone. Marks on all metal, including oily or wet surfaces.

FEATURES/BENEFITS:

- Marks on oily, wet or rusty metals, and will not scratch or abrade surfaces
- Available in flat and round shapes
- Durable, mechanical holder prevents stick breakage and features a convenient, built-in sharpener and pocket clip for easy storage.

| 96004 | Flat | 96018 | Flat Refill, 25 Pack |
|-------|-------------------|-------|-----------------------|
| 96006 | Round | 96002 | Flat Refill, 100 Pack |
| 96107 | Round & 6 Refills | 96007 | Round Refill, 6 Pack |

Soapstone Temporary marking for welding and metal fabrication

All-natural soapstone is the economical, versatile solution for temporary marking during welding operations. Marks are easily removed and will not contaminate welds.

FEATURES/BENEFITS:

- Temporary marks can be easily removed
- Marks will not contaminate weld or damage metal surface
- Holders for flat and round shapes reduce breakage

80129 Flat 80130 Round 80131 Square 80140 Flat Holder and Refills

Markal.com Tempil.com LACO.com

Tempilstik[®] The industry standard, original temperature-indicating stick

Available in over 100 temperature ratings from 100°F to 2000°F (38°C to 1093°C), each Tempilstik has a unique slip-resistant metal holder, specifically engineered for maximum user control. Precise for the most critical jobs, Tempilstik meets the preheat temperature requirements of AWS D1.1 and other welding code specifications. Our Tempilstik product line has been providing accuracy, confidence and compliance for over 70 years.

FEATURES & BENEFITS:

17700

- Results are +/- 1% of rated temperature.
- Melts at designated temperature for easy visual inspection.
- Unique slip-resistant metal holder secures stick and maximizes control.
- Fast results reduce set up and down time.
- Traceable: each marked by temperature, lot number and is NIST traceable
- Compliant: meets AWS D1.1, ASME Code Sec. I, III and VIII, ANSI/ASME Code B31.1 and B31.3.

| <u>Part No.</u> | | <u>°F</u> | | | |
|-----------------|-----|-----------|-------|------|------|
| 28000 | 38 | 100 | 28035 | 204 | 400 |
| 28300 | 40 | 104 | 28328 | 210 | 410 |
| 28002 | 43 | 109 | 28036 | 212 | 413 |
| 28004 | 48 | 119 | 28329 | 215 | 419 |
| | | | | | |
| 28301 | 50 | 122 | 28037 | 218 | 425 |
| 28005 | 52 | 125 | 28330 | 220 | 428 |
| 28302 | 55 | 131 | 28331 | 225 | 437 |
| 28303 | 60 | 140 | 28332 | 230 | 446 |
| 28006 | 66 | 150 | 28039 | 232 | 450 |
| 28304 | 70 | 158 | 28333 | 235 | 455 |
| 28007 | 73 | 163 | | | |
| | | | 28040 | 239 | 463 |
| 28305 | 75 | 167 | 28041 | 246 | 475 |
| 28008 | 76 | 169 | 28336 | 250 | 482 |
| 28009 | 79 | 175 | 28042 | 253 | 488 |
| 28306 | 80 | 176 | 28043 | 260 | 500 |
| 28010 | 83 | 182 | 28338 | 270 | 518 |
| 28307 | 85 | 185 | 28044 | 274 | 525 |
| | | | | | |
| 28011 | 87 | 188 | 28339 | 280 | 536 |
| 28308 | 90 | 194 | 28045 | 288 | 550 |
| 28012 | 93 | 200 | 28340 | 290 | 554 |
| 28309 | 95 | 203 | 28341 | 300 | 572 |
| 28013 | 97 | 206 | 28046 | 302 | 575 |
| 28310 | 100 | 212 | 28047 | 316 | 600 |
| 28014 | 101 | 213 | 28342 | 320 | 608 |
| 28015 | 101 | 219 | 28048 | 343 | 650 |
| | | | | | |
| 28016 | 107 | 225 | 28343 | 350 | 662 |
| 28312 | 110 | 230 | 28049 | 371 | 700 |
| 28313 | 115 | 239 | 28050 | 399 | 750 |
| 28314 | 120 | 248 | 28345 | 400 | 752 |
| 28019 | 121 | 250 | 28051 | 427 | 800 |
| 28020 | 124 | 256 | 28052 | 454 | 850 |
| 28315 | 125 | 257 | 28347 | 460 | 860 |
| 28021 | 128 | 263 | 28053 | 482 | 900 |
| 28316 | 130 | 266 | 28349 | 500 | 932 |
| | | | | | |
| 28022 | 132 | 269 | 28055 | 510 | 950 |
| 28023 | 135 | 275 | 28056 | 538 | 1000 |
| 28317 | 140 | 284 | 28057 | 550 | 1022 |
| 28024 | 142 | 288 | 28350 | 560 | 1040 |
| 28025 | 146 | 294 | 28058 | 566 | 1050 |
| 28026 | 149 | 300 | 28059 | 593 | 1100 |
| 28318 | 150 | 302 | 28351 | 600 | 1112 |
| 28027 | 152 | 306 | 28060 | 621 | 1150 |
| 28319 | 155 | 311 | 28352 | 625 | 1157 |
| 28028 | 156 | | | 649 | 1200 |
| | | 313 | 28061 | | |
| 28320 | 160 | 320 | 28062 | 677 | 1250 |
| 28029 | 163 | 325 | 28355 | 700 | 1292 |
| 28321 | 165 | 329 | 28063 | 704 | 1300 |
| 28322 | 170 | 338 | 28064 | 760 | 1400 |
| 28030 | 173 | 344 | 28065 | 788 | 1450 |
| 28323 | 175 | 347 | 28066 | 816 | 1500 |
| 28031 | 177 | 350 | 28067 | 843 | 1550 |
| 28324 | 180 | 356 | 28068 | 871 | 1600 |
| | | | | | |
| 28032 | 184 | 363 | 28069 | 899 | 1650 |
| 28325 | 190 | 374 | 28070 | 927 | 1700 |
| 28033 | 191 | 375 | 28072 | 982 | 1800 |
| 28326 | 195 | 383 | 28073 | 1038 | 1900 |
| 28034 | 198 | 388 | 28074 | 1066 | 1950 |
| 28327 | 200 | 392 | 28075 | 1093 | 2000 |
| | | | | | |

Certified Thermomelt[®] Nuclear pre-certified, accurate temperature indicating stick

Pre-certified to meet nuclear and military low-corrosion specifications for stainless-steel fabrication and other super alloys, the Markal Certified Thermomelt HEAT-STIK[®] is a quick method to accurately measure metal surface temperatures and equipment. The 20 available temperatures are lot traceable for jobsite documentation.

FEATURES & BENEFITS:

- Certified to meet the following U.S.A. and
 - international specifications:
 - EDF PMUC - MIL - STD-2041D
 - U.S. DOE RDT F-7-3T (expired)
 - U.S. Navy C3070
- Engineered to meet:
 - 200 ppm total halogens
 - 250 ppm each low melting point metals
 - 300 ppm total low melting point metals
 - 200 ppm sulfur
- Individual lot analysis and certification available at www.markal.com/certified for quick, accurate reference
- Protective holder, shirt-clip and adjustment ring prevents breakage and improves handling

SURFACE USES:

- Stainless Steel
- Alloy and superalloy metals

| Part No. | °C | °F |
|----------|-----|-----|
| 89100 | 38 | 100 |
| 89125 | 52 | 125 |
| 89150 | 66 | 150 |
| 89175 | 79 | 175 |
| 89200 | 93 | 200 |
| 89225 | 107 | 225 |
| 89250 | 121 | 250 |
| 89275 | 135 | 275 |
| 89300 | 148 | 300 |
| 89325 | 163 | 325 |
| 89350 | 177 | 350 |
| 89375 | 191 | 375 |
| 89400 | 204 | 400 |
| 89425 | 218 | 425 |
| 89450 | 232 | 450 |
| 89475 | 246 | 475 |
| 89500 | 260 | 500 |
| 89525 | 274 | 525 |
| 89550 | 288 | 550 |
| 89650 | 343 | 650 |

Markal.com Tempil.com LACO.com

| MAD | E | N |
|-----|---|---|
| | | |

Markal

Estik[™] Electronic Surface Thermometer

Developed by Tempil engineers for a wide range of critical temperature monitoring applications, our patent-pending Estik incorporates the latest in micro-thermocouple technology with a bold digital readout to instantly display the surface temperature with an accuracy of +/- 2%. Measuring surface temperature from 32°F to 999°F (0°C to 537°C), Tempil Estik can be used on polished or non-polished surfaces. Unlike other types of electronic technology, it is not necessary to know what the emissivity of the surface material is in order to obtain an accurate reading.

FEATURES & BENEFITS:

- Ergonomic hand grip
- Three-digit backlit display
- °C or °F selectable readout
- No wires or cables
- Automatic shut-off

500

24290 Estik 24251 Estik – NIST Certified 24252 Estik Thermocouple Band Replacement

Bloxide[®] Weldable Primer



Bloxide is a versatile, rust-preventive, weldable primer with a unique formula

that can be applied to a wide range of metals, preventing the formation of rust and corrosion during extended periods of storage. Bloxide eliminates the need to clean metal surfaces before welding due to its enhanced corrosion preventative features, thus saving time and labor costs during fabrication. Bloxide also improves the weld quality after application, resulting in X-Ray quality welds.

FEATURES & BENEFITS:

- Ideal for extended periods of outside steel storage
- Ability to strike welding arc without removal
- Temperature resistant to 800°F (427°C)
- Can be sprayed, brushed or parts can be dipped into it

24100 1 Gallon 24101 55 Gallon Drum 24102 5 Gallon Pail 24104 12 oz Aerosol Can

Anti-Heat[®] Heat Absorbing Compound

This exceptional, heat-absorbing compound is specially formulated to eliminate the heat damage and discoloration that often occurs on light gauge metals during fabrication. Once applied, Anti-Heat prevents the heat generated by welding, soldering or preheating from traveling beyond where the Anti-Heat is applied – thus preventing heat-related damages such as buckling, cracking, warping or other metal distortions.

FEATURES & BENEFITS:

- Non-toxic
- Harmless to the skin
- Asbestos-free and odorless

24000 5 Gallon Pail 24001 1 Gallon 24002 1 Quart 24003 2 oz Tube



Cool Gel[®] Heat Barrier Spray

Used to protect sensitive equipment and components from excess heat during pre-heating, interpass, welding, and post-heating applications. Cool Gel's unique, no-drip gelled formula evaporates within 48 hours, eliminating cleanup. Easier than using a heat blanket, Cool Gel provides assurance the job can be completed without costly heat damage.

FEATURES & BENEFITS:

- Reduces the risk of costly heat damage to sensitive equipment and components
- Protects painted and finished surfaces from discoloration due to torch heat
- Safe, non-toxic, harmless to skin, and odorless

11513 1 Pint 11509 1 Quart 11503 5 Gallon





12.4

XAX

Ð





LA-CO Industries Inc. 1201 Pratt Boulevard Elk Grove Village, IL 60007-5746 USA (1) 800.621.4025 (1) 847.956.7600 Customer_Service@laco.com

LA-CO Industries Europe S.A.S. ALLEE DES COMBES PI DE LA PLAINE DE L'AIN 01150 BLYES France Tel : +33 (0) 4 74 46 23 23 info@eu.laco.com



