

Nu-Calgon PRODUCT CATALOG

Quality Products for Air Conditioning, Refrigeration & Heating

Table of Contents

| Total System Protection | 1-3 |
|-------------------------------------|-------|
| Coil Cleaners and Sprayers | 4-10 |
| Indoor Air Quality | 11-14 |
| Gas Leak Detectors | 15 |
| Refrigeration Oil & Vacuum Pump Oil | 16-17 |
| Aerosol Products | 18-20 |
| Specialty Products | 21-22 |
| Insulation Products | 23 |
| Glycol & Closed Systems | 24-25 |
| Water Treatment & Plumbing Products | 26-30 |
| Water Filtration Maintenance | 31 |
| Water Filtration | 32-33 |
| Nu-Plus by Everpure | 34-39 |
| Training Classes | 40 |





45

40

35 30 25

15

20

Compatible with All Refrigerants & Oils

Easiest to Install

READY

SEAL!

SET

Permanent Seal

Takes seconds to inject.

No injection hose or caulk gun needed.

Concentrated formula means less material in the system.

The Next Generation of Refrigerant Leak Sealant



EasySeal® Direct Inject

EasySeal Direct Inject is a new generation of sealants. Its innovative injection method makes it easier to install than other sealants. With this new injection system, pumping down the unit is a thing of the past. EasySeal Direct Inject works with all refrigerants and oils. Concentrated formula means less material in system. It is perfect for split systems, heat pumps, microchannel coils, packaged units, and mini splits. EasySeal Direct Inject is formulated to not plug cap tubes or expansion valves.

| EasySeal Direct Inject | 4050-08 |
|------------------------------------|---------|
| EasySeal Direct Inject bulk 6-pack | 4050-07 |
| EasySeal-SS Direct Inject | 4050-05 |



A/C EasySeal®

A/C EasySeal prevents and seals refrigerant leaks in residential and light commercial ACR systems. It is perfect for those hard-to-find and expensive-to-fix leaks and works with all refrigerants (except ammonia). It is easily installed with the reusable piercing valve and hose. A/C EasySeal circulates with the system's refrigerant, and if a leak should occur, it will quickly and permanently seal the leak and prevent the system from losing refrigerant and shutting down.

| A/C EasySeal | 3 ounce pressurized can - treats 1.5 to 5 ton systems | 4050-06 |
|-----------------------------|---|---------|
| A/C EasySeal-SS | 1.25 ounce pressurized can - treats fractional to 1.5 ton systems | 4050-01 |
| "2+1" Display Pack | 2 cans of A/C EasySeal and an A/C Piercing Valve and Hose | 4050-02 |
| A/C EasySeal-XL | Treats systems with refrigerant charge of 125 lbs. – 250 lbs. | 4050-10 |
| A/C Piercing Valve and Hose | | 4051-99 |



A/C EasyDry

This product is a quick and simple way to prevent and eliminate moisture in a system. A/C EasyDry contains a dehydrating agent that converts system moisture into a natural organic material that is compatible with and mixes with the lubricant. It is great for preventing acid formation, which is caused by moisture in a system, and it works with all refrigerants (except ammonia). Each can will treat up to a 5 ton system and is easily installed with the reusable piercing valve and hose.

| 3 ounce pressurized can | 4051-06 |
|-----------------------------|---------|
| A/C Piercing Valve and Hose | 4051-99 |

Total System Protection



R_x11-flush®

R_x11-flush is a unique solvent engineered specifically for flushing refrigeration and air conditioning systems. R_x11-flush is ozone-safe, non-toxic, and non-flammable. Used exactly like the old R-11 flushing process, its patented HFC-based solvent formulation is powerful enough to flush away sludge, carbon residues, oils, acids, water and other particulates. R_x11-flush is ideal for system flushing after burnouts, during retrofits and for flushing line sets for R-410A conversions. R_x11-flush has been the industry's standard for over a decade, and contractors agree — it's the best flush for R-410A retrofits and after compressor burnouts.

| Rx11-flush Starter Kit | Contains a 1 lb. canister, Rx11-flush Gun and Hose, and Injection Valve | 4300-08 |
|------------------------|---|---------|
| 1 lb. canister | Recommended for a 3-4 ton system | 4300-09 |
| "2+1" Display Pack | Contains one Injection Valve and two 2 lb. canisters | 4300-10 |
| 2 lb. canister | Recommended for a 5-7 ton system | 4300-11 |
| 13 lb. canister | Recommended for up to 50 ton system | 4300-15 |
| 26 lb. canister | Recommended for systems over 50 tons | 4300-26 |



R_X11-flush[®] Liquid

R_X11-flush Liquid is a new and improved chemistry that is the next generation in flushing technology. It remains a constant boiling solvent, and its stronger, fasteracting formula dissolves more oil, moisture and contaminants than any other flush. It is ideal for line sets, burnouts, and other flushing requirements.

| 19.5 ounce can | 4300-30 |
|-------------------------------|---------|
| Rx11-flush Liquid Starter Kit | 4300-38 |



R_X11-flush[®] Accessories

The R_X11-flush product family also includes various support tools. This includes the Injection Valve for hooking up to a charging hose for flushing and the Flushing Tool for facilitating line set flushing. In addition, the R_X11-flush Gun with a built-in flushing attachment and the R_X11-flush Hose (24") are available.

| Flushing Tool | 4300-50 |
|-----------------------|---------|
| Rx11-flush Gun | 4300-51 |
| Rx11-flush Hose (24") | 4300-52 |
| Injection Valve | 4300-89 |

(Injection Valve fits Pneu-flush® and pressurized Rx-Acid Scavenger® as well)

Total System Protection



A/C Re-New®

A/C Re-New is a highly formulated, OEM approved product that has established an outstanding track record enhancing the performance of air conditioning and refrigeration systems. A/C Re-New frees sticky valves, quiets noisy compressors, reduces energy consumption by lowering starting and running amps, and improves heat transfer in the evaporator and condenser. It's great for new systems as a preventative or to reinstate performance of older systems.

| 1 quart can | 4057-54 | |
|--------------------------|---------|--|
| 4 fluid ounce can | 4057-55 | |
| A/C Re-New Injector Tool | 4057-99 | |



Rx-Acid Scavenger®

The most effective way to neutralize or "scavenge" acid in refrigeration and air conditioning systems. It is perfect for use after burnouts or during normal on-going system maintenance. In addition, Rx-Acid Scavenger can be used with all lubricants: mineral, alkylbenzene and polyol ester. Now available in a pressurized can for easy injection into charged systems or hermetically sealed systems.

| 2 fluid ounce unpressurized bottle | 4301-02 |
|------------------------------------|---------|
| 3.8 ounce pressurized can | 4301-05 |
| Injection Valve | 4300-89 |

(Injection Valve fits R_X11-flush[®] and Pneu-flush[®] as well)



Phase III[®] Refrigeration Oil Acid Test Kit

Formulated for use with POEs as well as mineral oils and alkylbenzene, Phase III is an inexpensive, disposable test kit that provides proof-positive that acid level in refrigeration oil is either safe or unsafe. Phase separation makes it easy to see change in color of acid indicator (even if a leak detection dye has been added to the oil). Just two bottles to work with, it is simple, safe, accurate, and small enough that you can carry several in your tool box.

1 each

4320-W8

How to Test Oil with Phase III®

- 1. Pour the solution from the small bottle into the large bottle. The bottom layer of this mixture will be purple.
- 2. Completely fill the small bottle with oil from the unit being tested. Do this immediately after the oil is removed from the crankcase, since exposure to air will contaminate the oil and give a false test result.
- 3. Pour the oil into the large bottle and shake well.
- Wait two to three minutes. A phase separation will develop as the oil rises to the top of the mixture and an aqueous layer forms on the bottom.
- 5. If the bottom layer:
 - Stays purple- the oil is satisfactory. Turns light pink or loses color completelythe oil has higher than acceptable acid content.



Coil Cleaner Selection Guide

| Nu-Calgon Coil Cleaners Found on Pages 6-7 | Nu-B | Brite® | Foam-Brite® | Alka-Brite® Plus | Cal-Brite® | Tri-Pow'r® HD | CalCle | ean® | Special HD CalClean® | TriClean [™] 2x | Nu-Solve [™] NR |
|---|---------|-------------|---------------|------------------|------------|---------------|---------|--------|-------------------------|--------------------------|--------------------------|
| | | / | $\overline{}$ | | | | | / | | | \bigtriangledown |
| | | | | EQUIPM | IENT USE | D ON | | | | | |
| Condenser Coils | | | • | • | • | • | • | • | • | • | • |
| Mini-Split Condenser Coils | | | | | | • | • | • | • | • | • |
| Small Condenser Coils | | | • | • | • | • | • | , | • | • | • |
| Evaporator Coils | | | | | • | • | • | • | • | | |
| Mini-Split Evaporator Coils | | | | | | • | • |) | • | | |
| Small Evaporator Coils | | | | | • | • | • | • | • | | |
| Microchannel Coils | | | | | | • | • | • | • | • | • |
| Electronic Air Filters | | | | | | | | | • | | |
| Fan Blades, Permanent Filters | | | | | • | • | • | , | • | • | • |
| | | | F | ORMULA | TED TO F | REMOVE | | | | | |
| Greasy Dirt & Oil | • | • | ٠ | • | • | • | • | , | ٠ | • | • |
| Cooking Grease | • | • | • | • | | • | | | • | | • |
| Lint, Dust, Dirt & Grime | • | • | ٠ | • | • | • | • | , | • | • | • |
| Tobacco Tars | | | | | | | | | • | | |
| Oxide (Corrosion) Deposits | • | • | • | • | • | | | | | | |
| Cottonwood/ Bugs | • | • | • | • | • | | | | • | | |
| | | | | FEATUR | ES & BEN | EFITS | l | | | | |
| Product Type | Alka | line | Alkaline | Alkaline | Acidic | Alkaline | Alka | line | Alkaline | Alkaline | Alkaline |
| Foaming | Aerosol | Liquid • | • | • | • | | Aerosol | Liquid | | | |
| Brightening | • | • | • | • | • | | | | | | |
| Degreasing | • | • | • | • | • | • | • | • | • | • | • |
| EPA Registered Disinfectant | | | | | | | | | | | |
| No Rinse (Evaporators) | | | | | | •* | | •* | •* | | |
| No Rinse (Condensers) | | | | | | | | | | | • |
| Biodegradable | • | • | • | • | • | • | | • | • | • | • |
| USDA Authorized | • | • | | | | | | • | • | | |
| U.S. EPA's Safer Choice Program | | | | | | | | | | | |
| NSF Registered | | ٠ | • | • | | • | • | | | • | |

* Dilution ratios for no rinse applications: Tri-Pow'r HD = 10:1, Liquid CalClean = 10:1 (Aerosol CalClean must be rinsed), Special HD CalClean = 40:1, Green Clean = 10:1

Coil Cleaner Selection Guide



Condenser Coils

Evaporator Coils

Mini-Split Condenser Coils

Mini-Split Evaporator Coils

Small Evaporator Coils

Microchannel Coils

Electronic Air Filters

Permanent Filters

Greasy Dirt & Oil

Cooking Grease

Tobacco Tars

Product Type

Foaming

Brightening Degreasing

Lint, Dust, Dirt & Grime

Oxide (Corrosion) Deposits

EPA Registered Disinfectant

No Rinse (Evaporators)

No Rinse (Condensers)

Biodegradable

U.S. EPA's

USDA Authorized

Safer Choice Program **NSF Registered**

Cottonwood/ Bugs

Fan Blades.

Small Condenser Coils



•

•

•

•

•

Alkaline

Aerosol Liquid

•

•

•

•

•

•

.

•

•

•

•

•

•

Alkaline

•

•

.



•

.

•

.

•

•

Alkaline

•

.



Evap-Green[™]

EQUIPMENT USED ON

•

•

-

•

•

FEATURES & BENEFITS

Alkaline

•

•

•

Visit us at www.nucalgon.com or call 1-800-554-5499

FORMULATED TO REMOVE



•

.

•

.

•

.

.

•

•

Alkaline

•

•*

•

•

•

•

•

•

.

•

•

Alkaline

•

•

•



CompleteCare Mini-Split Kit

Coil Cleaner Selection Guide

Nu-Blast® & Cal-Blast®

•

•

•

•

•

•

•

•

Solvent

.

•

•

•

•

•

•

Alkaline

.

•

•

•

5

Blackhawk®

•

.

•

.

•

.

.

.

•

•

•

Alkaline

.

•

•

•



Nu-Brite®

Nu-Brite is the most effective coil cleaner available today. It foams, brightens, and is an equally effective yet safer alternative to HF acidbased products. It produces a high volume of foam that cleans more effectively than acids, particularly in removing grease. Biodegradable. The liquid versions are USDA approved and NSF registered.

| 18 ounce can | 4291-18 | |
|-----------------|----------|-----|
| 1 gallon bottle | 4291-08 | NCE |
| 2.5 gallon pail | 4291-05* | NJF |
| 55 gallon drum | 4291-01 | |







Foam-Brite®

The ultimate in foaming alkaline cleaners, Foam-Brite cleans and brightens while at the same time providing tremendous foaming to push dirt and grime out of the coil. Can easily be used in place of the more dangerous HF acid-based products. Biodegradable. NSF registered.

| 1 gallon bottle | 4178-08 | \frown |
|-----------------|----------|---------------|
| 2.5 gallon pail | 4178-05* | (NSF) |
| 55 gallon drum | 4178-01 | $\overline{}$ |

Alka-Brite® Plus

A non-acid, alkaline based product for brightening and cleaning air-cooled condensers, Alka-Brite Plus contains the best available detergents to quickly penetrate and remove oxidation. Its foaming action helps to lift greasy soils out of the coil. Biodegradable. NSF registered.

| 1 gallon bottle | 4120-08 | |
|-----------------|----------|-------|
| 2.5 gallon pail | 4120-05* | (NSF) |
| 55 gallon drum | 4120-01 | |

Cal-Brite®

Cal-Brite is a low pH cleaner developed for cleaning evaporator coils, air-cooled condensers and other finned cooling and heating coils. Its versatility is based upon glycolic acid and other unique ingredients. It provides moderate foaming and brightening and is safe for use indoors as well as outdoors. It's particularly suitable when lime scale must be removed from outdoor coils.

| 1 gallon bottle | 4133-08 |
|-----------------|---------|
| 55 gallon drum | 4133-01 |

* A 2.5 gallon pail wrench is also available. Part Number ZE64.













TriClean 2x[™]

The new way to clean a condenser coil. Simply connect to hose, clean, and rinse. TriClean 2x is metal-safe, designed for rapid emulsion of soils from the coil. Restores efficiency and is ideal for painted fin and microchannel coils. Eliminates the need for a sprayer.

| 1 quart sprayer with hose connector 4372-24 | NSF | F) |
|---|-----|----|
|---|-----|----|

Nu-Solve™ NR

Ready-to-use, non-rinse condenser coil cleaner for situations with limited water availability for rinsing. Nu-Solve NR is also for other applications where it is desirable to have less diluted cleaning solution on a commercial roof or when a solvent-based aerosol approach is not practical. Nu-Solve NR effectively emulsifies dirt and grime and provides a benefit of leaving a protective treatment on the aluminum for added corrosion protection, making the next cleaning easier. Nu-Solve NR can be applied with Nu-Calgon's poly sprayer or the Nu-Solve NR Sprayer (page 10).

| 1 gallon bottle | 4295-08 |
|-----------------|---------|
|-----------------|---------|

Tri-Pow'r® HD

An outstanding general purpose coil cleaner, providing detergency and degreasing as well as deodorizing capability. Its positive emulsion technology is very effective against oily grime as it converts the deposits into a more fluid or liquid form that can be easily rinsed away. It is non-acid, non-toxic, and biodegradable. NSF registered. Also great for microchannel coils.

| 1 gallon bottle | 4371-88 | NCE |
|-----------------|---------|-------|
| 55 gallon drum | 4371-81 | (NSF) |

CalClean®

An alkaline detergent formulated for cleaning evaporator coils, air-cooled condenser coils, metal filters, fan blades, and other surfaces soiled with grease, dust and dirt. Biodegradable. USDA approved. Aerosol is NSF registered. Also great for microchannel coils.

| 20 ounce can | 4081-75 (NSF) |
|-----------------|---------------|
| 1 gallon bottle | 4135-08 |
| 2.5 gallon pail | 4135-06* |
| 55 gallon drum | 4135-01 |

Special HD CalClean®

The best non-foaming cleaner available. Specifically formulated to remove tobacco tars from electronic air cleaners as well as the most stubborn deposits from finned coils. USDA approved. Also great for microchannel coils.

| 1 gallon bottle | 4143-08 |
|-----------------|----------|
| 2.5 gallon pail | 4143-06* |
| 55 gallon drum | 4143-01 |

* A 2.5 gallon pail wrench is also available. Part Number ZE64.

Evap Pow'r®-C

A no-rinse product formulated for cleaning evaporator coils. It is metal-safe, and it cleans and emulsifies even the most stubborn soils and deposits. Biodegradable. USDA approved. Also great for microchannel coils.

| 1 gallon bottle | 4168-08 |
|-----------------|----------|
| 2.5 gallon pail | 4168-05* |
| 55 gallon drum | 4168-01 |



Evap Foam No Rinse®

Evap Foam No Rinse is a high-performing, heavy-duty detergent. It is formulated with special surfactants and alkaline cleaners that have been developed into a foaming, no-rinse product. Evap Foam is ideal for use on most coils, but it is particularly suited for use on cooling or evaporator coils. The aerosol can be sprayed either right side up or upside down. NSF registered. Can be used with Talon Flexible Aerosol Wand (4776-0) for hard to reach locations (see page 18).

| 18 ounce can | 4171-75 | NSF |) |
|--------------|---------|-----|---|
|--------------|---------|-----|---|



Evap-Fresh® No Rinse Evaporator Coil Cleaner & Disinfectant

Evap-Fresh is a ready-to-use, no-rinse cleaner and disinfectant for evaporator coils. It effectively cleans as well as kills mold and bacteria. This one-step no-rinse disinfectant cleaner is perfect for air conditioners, commercial air handling units, HVAC cooling coils, refrigeration equipment, and evaporator coils. EPA registered specifically for use on HVAC equipment.

| 18 ounce can | 4166-75 |
|-----------------|---------|
| 1 gallon bottle | 4166-08 |

The following products are part of Nu-Calgon's Environmentally Friendly Green Select line. These coil cleaners meet the U.S. EPA Safer Choice Program standards, making them a safer choice for the user and the environment.





Cal-Green[™] Condenser Cleaner

Cal-Green is a plant-based, natural condenser cleaner that is powerful enough to remove dirt, grease, and grime. It meets the U.S. EPA Safer Choice Program standards, making it a safer choice for the user and the environment. This non-foaming, non-toxic concentrate is perfect for cleaning residential or commercial systems and restores their efficiency while being environmentally responsible. Also OEM approved for microchannel coils.

| 1 gallon bottle | 4190-08 |
|-----------------|---------|
| 55 gallon drum | 4190-01 |



Evap-Green™ Evaporator Cleaner

Evap-Green is a no-rinse product that is perfect for numerous heating and air conditioning applications, such as evaporator coils, roof top units, window units, metal filters, fan blades, and more. Evap-Green meet the U.S. EPA Safer Choice Program standards, making it a safer choice for the user and the environment . Evap-Green is also biodegradable and will not harm plants, animals, and aquatic life. Metal-safe — meets OEM guidelines for all aluminum coils, including microchannel types.

| 1 gallon bottle | 4191-08 |
|-----------------|---------|
| 55 gallon drum | 4191-01 |



Green Clean

A pleasantly scented, all-purpose, environmentally friendly cleaner designed for the rapid removal of grease and other heavy soils. It can be used right out of the bottle or diluted for milder jobs. Biodegradable. Also great for microchannel coils.

| 4186-24 | 1 quart spray bottle |
|---------|----------------------|
| 4186-08 | 1 gallon bottle |
| 4186-01 | 55 gallon drum |
| 4180-01 | 55 gallon druin |



Blackhawk®

Blackhawk is an expanding foam coil cleaner. Formulated to deeply penetrate the coil, it liquefies to quickly remove grease, grime, or oily soils from deep within the coil. Blackhawk's formulation is safe and problem-free for cleaning evaporator or condenser coils in an occupied building; produces no objectional fumes. It is particularly effective on coils on refrigerators, coolers, and freezers located in restaurants and other commercial establishments. NSF registered. **Can be used with Talon Flexible Aerosol Wand (4776-0) for hard to reach locations (see page 18).**

| 18 ounce can | 4127-75 | (NSF) |
|--------------|---------|-------|
|--------------|---------|-------|

Nu-Blast®

Cal-Blast®

20 ounce can

with excellent solvency and blasting spray.

A no-rinse condenser coil cleaner in a convenient aerosol package. Double action of highpressure blast and solvent cleaning restores design efficiency of condenser coils. It is non-flammable and non-conductive. No rinse required — cleaning solvent evaporates completely. Use with adequate ventilation.

| 18 ounce can | 4290-75 |
|--------------|---------|
|--------------|---------|

Cal-Blast is a no-rinse condenser cleaner that will powerfully separate undesirable materials

from the surface, offering maximum cleaning of finned coils. It's a high-performance aerosol

4132-20



Coil Protectants



DuraCoil

DuraCoil is a long-lasting coating for coils and surfaces in corrosive environments. It uses a durable, OEM-approved Heresite[®] Coating. DuraCoil has a fast, air-dry formula that bonds to all metals and causes negligible heat transfer loss across the coil. Great for repairing an OEM-approved coil coating that has been compromised while in service! Brown in color.

| 11 ounce can 4083-90 |
|----------------------|
|----------------------|

Cal-Shield[®]

Cal-Shield is a synergistic liquid formulation based upon DuPont's Teflon[®] fluoro-additives. It's designed for application on air-cooled condensers, evaporator coils, and other finned heating and cooling coils. Cal-Shield will shield and protect the coil from adverse conditions.

| 1 quart spray bottle | 4148-32 |
|----------------------|---------|
| 1 gallon bottle | 4148-08 |



Nu-Shield®

Nu-Shield, the newest generation of chemistry for protecting coils and other surfaces, is a super-hydrophobic (water repelling) product. The non-conductive formula has numerous applications in the management of water on non-food, non-potable water surfaces for the HVACR trade. Simply spray it on and watch the water bead up and roll right off.

9 ounce can

4294-75



Sprayers



Coil Gun®

A "hose-end" sprayer that features five different mix ratio settings designed for coil cleaners. Utilizes a 2 quart capacity bottle and includes a foam wand as well as "quick disconnect" capability. The Coil Gun Probe accessory has a 90° direction of spray that allows cleaning from inside the coil. It also provides easy access in tough-to-reach locations.

| Coil Gun | 4774-0 |
|----------------|--------|
| Coil Gun Probe | 4774-1 |



Coil Mate™ Coil Cleaning Hose

Durable 5/8 inch diameter reinforced hose with Flex-Guard protection. The 50-foot hose is equipped with solid brass wrench fittings. The Coil Mate is a necessity when using the popular Coil Gun[®] or rinsing an air-cooled coil with water after using a Nu-Calgon coil cleaner.

| Coil Mate | 61231 |
|----------------------------|-------|
| Hot Water Hose | 61238 |
| Plastic Pistol Grip Nozzle | 61241 |



Nu-Solve NR Sprayer

Backpack-type sprayer developed for applying Nu-Solve NR, a non-rinse outdoor coil cleaner when water availability for rinsing is an issue. Sprayer utilizes a fourgallon tank with no holes or connections at the bottom to leak! Provides high-pressure spray for added cleaning effectiveness, large pressure chamber for lasting pressure, and a flexible and rugged wand with an adjustable spray nozzle.

4775-0



1 each



No. 50P Poly Sprayer

1 each

The No. 50P is constructed of highdensity translucent polyethylene. It has a half gallon (3 pint) capacity. The nozzle is adjustable and the flow rate is controlled by a thumb lever. It comes with a 7["] polyethylene pump.

4770-0

| adjustable n and a pressu |
|------------------------------|
| 1 each |
| |
| |
| |
| |
| |
| |
| |
| |
| |

No. 220CP Poly Sprayer

The No. 220CP Poly Sprayer is constructed of high-density translucent polyethylene with a funnel top that provides easy chemical pouring. This 2 gallon capacity sprayer features an easy fill level indicator and comes with an 8" pump and a high resin plastic adjustable nozzle with three feet of hose.

| 1 each | 4771-3 |
|--------|--------|
| | |



No. 100P Poly Sprayer

This sprayer is constructed of highdensity translucent polyethylene. It has a funnel top for easy chemical pouring and a 1 gallon working capacity. It comes with a 8" polypropylene pump, brass handle and extension tube with adjustable nozzle, a wear-resistant hose, and a pressure relief valve.



No. 300P Poly Sprayer

The No. 300P Poly Sprayer is constructed of high-density translucent polyethylene. It has a funnel top and a 3.5 gallon capacity (3 gallon working capacity). It comes with a 10[°] Celcon pump, brass extension tube with adjustable nozzle, and five feet of vinyl hose.



No. 200P HiPressure Poly Sprayer

The No. 200P HiPressure Poly Sprayer is constructed of high-density translucent polyethylene. It has a 2 gallon working capacity, funnel top, pump handle, and all-brass hardware. No pumping is required. Pressurize the sprayer with water through a "quick disconnect" fitting.

| 1 each | 4771-2 |
|--------|--------|
|--------|--------|



Multi-Purpose Sprayer

A 24 ounce capacity sprayer. It is ideal for small cleaning jobs, such as window units and water coolers.

1 each 4772-0

Indoor Air Quality













ClenAfr

Evap-Fresh® No Rinse Evaporator Coil Cleaner & Disinfectant

Evap-Fresh is a ready-to-use, no-rinse cleaner and disinfectant for evaporator coils. It effectively cleans as well as kills mold and bacteria. This one-step no-rinse disinfectant cleaner is perfect for air conditioners, commercial air handling units, HVAC cooling coils, refrigeration equipment, and evaporator coils. EPA registered specifically for use on HVAC equipment to kill H1N1 and other viruses such as Norwalk, Rhoto, Hepatitis, Rabies MRSA, and more.

| 18 ounce can | 4166-75 |
|-----------------|---------|
| 1 gallon bottle | 4166-08 |

CompleteCare Mini-Split Kit

The CompleteCare Mini-Split Kit cleans, disinfects, and deodorizes mini-splits, as well as controls mold and mildew. It also protects condensate pans and lines from plugging. Each kit treats 2-3 mini-splits. Contains one 18 oz. can of Evap-Fresh No Rinse and one PurCool® Green Mini Strip.

1 each 4151-08

Bio-Fresh® cd

A ready-to-use bacteriostatic, fungistatic, and deodorizer based upon chlorine dioxide technology. Inhibits the growth of bacteria, mold, mildew, fungi, and yeasts in IAQ applications, and it may be applied to occupied spaces. Its EPA registration applies to HVACR ventilating equipment, including coils, condensate pans, filters, and duct-work. Easily applied by spraying, brushing, sponging, or wiping. EPA registered.

| 1 quart spray bottle | 4126-34 |
|----------------------|---------|
| 1 gallon bottle | 4126-38 |

Bio-Fresh® Fogger

The Bio-Fresh Fogger is made of a one-piece, seamless heavy-duty copolymer. It uses a 48["] flexible hose and is adjustable from 0-18 ounces per minute with the respective particle size at 20 to 80 microns. It's ideal for spraying Bio-Fresh cd in duct work and large areas.

| 1 each | 4693-0 |
|--------|--------|
|--------|--------|

Drain Solve

Ideal for condensate pan drains. Drain Solve saves time and money with its ease of use. It eliminates application concerns associated with more reactive, fuming drain openers. Simply pour it down the drain and let it work without fear of noxious fumes or reactions. Does not contain sulfuric acid.

| 1 quart | 4165-24 | NSF |
|----------|---------|-----|
| 1 gallon | 4165-08 | Mar |

A/C Drain Sucker®

A/C condensate drain pan overflow is caused by slime and sludge that builds up and clogs the drain line. The A/C Drain Sucker quickly removes the clog and the excess water, resolving the overflow problem. The kit includes a PurCool[®] Pan Strip to provide months of preventive treatment and free flowing drains, as well as all fittings and hoses for suction or pressure applications.

| | Nu-Calgon Number | ClenAir Number |
|--|------------------|----------------|
| A/C Drain Sucker kit | 61308 | CADS1 |
| PurCool Pan Strip - treats 3 tons - 6 mos. | 61043 | 1903D |

ClenAir.





lep4





The Original ClenAir[™] Odor Neutralizer

ClenAir's unique odor neutralizing formula removes odors quickly and permanently. It is a true odor eliminator, not a mask. Originally designed for use in central air systems, on fire and flood restoration jobs and in sewage facilities, ClenAir is a professional product, yet it leaves no lingering antiseptic or perfume smell. It is great for odors caused by fuel oil, smoke, pets, mold and mildew, cigarette and cigar smoke, decay, cleaning solvents and even skunks. ClenAir has three different scents: Original, CherryAir, and OrangeAir. The scents come in multiple sizes for multiple applications.

| Original | Nu-Calgon | ClenAir | Original | Nu-Calgon | ClenAir |
|-------------------------|-----------|---------|--------------------------------|-----------|---------|
| Mini Tub | 61000 | CA1500M | 10 lb. Tub | 61005 | 1510 |
| 1/2 lb. Tub display box | 61001 | 1500D | 30 lb. Tub | 61006 | 1530 |
| 1/2 lb. Tub | 61002 | 1500 | Wall Unit (White) | 61007 | 1300 |
| 1 lb. Tub | 61003 | 1501 | Gel Brick for Wall Unit (1lb.) | 61008 | 1401 |
| 3 lb. Tub | 61004 | 1503 | | | |
| | | | | | |
| CherryAir | Nu-Calgon | ClenAir | CherryAir | Nu-Calgon | ClenAir |
| Mini Tub | 61018 | CA1800M | 3 lb. Tub | 61013 | 1803 |
| 1/2 lb. Tub display box | 61010 | 1800D | 10 lb. Tub | 61015 | 1810 |
| 1 lb. Tub | 61011 | 1801 | 30 lb. Tub | 61017 | 1830 |
| | | | | | |
| OrangeAir | Nu-Calgon | ClenAir | OrangeAir | Nu-Calgon | ClenAir |
| Mini Tub | 61028 | CA1300M | 3 lb. Tub | 61023 | CA1303 |
| 1/2 lb. Tub display box | 61020 | CA1300D | 10 lb. Tub | 61025 | CA1310 |
| 1 lb. Tub | 61021 | CA1301 | 30 lb. Tub | 61027 | CA1330 |
| | | | | | |

HVAC Odor Block®

ClenAir HVAC Odor Block is not a perfume mask or cover-up. The unique ClenAir formula molecularly reacts with the airborne odor-causing compounds and eliminates them and other indoor pollutants, leaving clean, fresh, air behind. The HVAC Odor Block makes it easy to remove odors and improve the indoor air quality in the entire home or building by treating the air through the HVAC system. Use in A/C units, furnaces, rooftop units, fan coil units, and air handlers. Part numbers 61060 and 61061 last up to 3 months. The HVAC Odor Block XL (61070) lasts up to 6 months.

| | | Nu-Calgon Number | ClenAir Number |
|---|--------------------------------|------------------|----------------|
| 1 | Residential HVAC Odor Block | 61060 | 1502 |
| | Residential HVAC Odor Block XL | 61070 | |
| | Commercial HVAC Odor Block | 61061 | CA1015 |



ClenAir Liquid Formula

ClenAir Liquid is a fast acting deodorizing product. It eliminates odors via an oxidation process while leaving a fresh scent. Applications include HVACR equipment, such as evaporator coils, duct work, condensate pans, refrigeration cases, reach-ins, and walk-in boxes. It can also be poured down drains, garbage disposals, and in trash cans. Spray in restrooms, locker rooms and on fouled carpeting and upholstery. Used by hospitals, nursing homes, and HVACR technicians.

| | Nu-Calgon | ClenAir |
|-------------------------|-----------|---------|
| Unscented Spray 16 oz. | 61030 | 1600D |
| Unscented Liquid 1 gal. | 61031 | 1610 |
| Citrus Spray 16 oz. | 61033 | 1700D |

| | Nu-Calgon | ClenAir |
|-------------------------|-----------|---------|
| Citrus Liquid 1 gal | 61035 | 1710 |
| CherryAir Spray 16 oz. | 61037 | 1900D |
| CherryAir Liquid 1 gal. | 61038 | 1910 |

Indoor Air Quality



Gel Tabs - Condensate Drain Pan Treatment

Formulated with a breakthrough technology for treating air conditioning drain pans and lines. Keeps the drain pan from clogging and eliminates foul and musty odors. When activated by condensation, the tablet will turn to gel and lock into place. Dissolves continuously and completely with nothing left to remove for up to three months. Stack together to increase duration.

| 3 ton tab (12 in tube) | 4185-03 | 5 ton tab bulk (100) | 4185-06 |
|------------------------|---------|----------------------|---------|
| 3 ton tab bulk (200) | 4185-04 | 15 ton tab (1 each) | 4185-15 |
| 5 ton tab (6 in tube) | 4185-05 | 20 ton tab (1 each) | 4185-20 |



PanPads

A product formulated to eliminate the build-up of bacteria and slime growths in air conditioning and refrigeration condensate drain pans. In laboratory tests, it has been proven effective against a wide spectrum of harmful bacteria, including Legionella. The product is EPA registered for this application. NSF registered.

| 5 (up to 5 tons) | 4295-34 | (NSF) | 15 (up to 15 tons) | 4296-24 | (NSF.) |
|-----------------------|---------|-------|--------------------|---------|--------|
| 5 Slim (up to 5 tons) | 4295-36 | MOL | 45 (up to 45 tons) | 4296-45 | MOL |



Pan-Treat®

Pan-Treat condensate tablets control odors and prevent overflows caused by plugged condensate drain lines. They can also be used in humidifiers. They are very easy to use, as well as non-corrosive, non-toxic, and biodegradable.

| 1 bottle (200 tablets) | 4296-60 |
|------------------------|---------|
| | |



PurCool® Strips

PurCool Strips keep A/C and refrigeration condensate drain pans clean and free flowing. Use PurCool Strips to prevent condensate drain clogs, costly overflows, and corrosion. Just place them anywhere in the drain pan where the PurCool Strip will contact the condensate water and enjoy up to six months of economical protection. PurCool Strips will adhere to the drain pan and will not float or move. Dissolves completely, leaving no residue. Safe for metal and plastic drain pans.

| | Nu-Calgon | ClenAir | | Nu-Calgon | ClenAir |
|------------------------|-----------|-----------|--------------|-----------|---------|
| 3 ton strip | 61043 | 1903D | 10 ton strip | 61041 | 2003D |
| 3 ton strip bulk (100) | 61047 | 1903D-100 | 30 ton strip | 61040 | 2009 |
| 5 ton strip | 61042 | 2001D | | | |

Indoor Air Quality: ClenAir by Nu-Calgon



PurCool® Green Strips and Tablets

PurCool® Tablets

1 bottle (200 tablets)

PurCool Strips/Tablets prevent slime, sludge, odors, and overflow of condensate pans. Time release formula adheres to pan and fully dissolves over time. PurCool Green Strips/Tablets use plant-based suspending and dispersing action to keep drain pans clean and free flowing. Products are available for commercial, residential, and mini split applications. Sizes are based on system tonnage, with each strip/tablet lasting up to six months.

| | Nu-Calgon Number | ClenAir Number |
|---------------------------------------|------------------|----------------|
| PurCool Green Mini Strip | 61044 | PCG5MS |
| PurCool Green Commercial Strip 10 ton | 61045 | PCG10T |
| PurCool Green Commercial Strip 30 ton | 61046 | PCG30T |
| PurCool Green 3 ton tablet | 61048 | |
| PurCool Green 3 ton bulk (200) | 61049 | |
| PurCool Green 5 ton tablet | 61051 | PCG5T |
| PurCool Green 5 ton bulk (100) | 61052 | PCG5T-100 |

PurCool Tablets utilize a powerful formulation to keep condensate drain pans clean and free flowing. Use PurCool Tablets to remove sludge and slime in A/C condensate pans to prevent costly water damage caused by overflows. They will control clogs, build-up, odors, and

61053

Nu-Calgon Number

ClenAir Number

PC200



Clen/fi





corrosion in drain pans, condensate pumps, and humidifiers.

HVAC Carbon Block is an add-on carbon purifier for all HVAC systems. Improves indoor air quality by removing odors, indoor air pollutants, and VOCs. Treats up to 10 tons for up to nine months.

| | Nu-Calgon Number | ClenAir Number |
|-------------------|------------------|----------------|
| HVAC Carbon Block | 61062 | CACB10 |





Humidifier Panel[™] Replacements

ClenAir Universal Humidifier Panels provide optimum moisture output, performance, and durability. They replace Aprilaire, Honeywell, Carrier, Bryant, Lennox, ICP, and others. Ultra Upgrade Humidifier Panels' material retains water, increasing moisture output and reducing water waste by up to 50%. They replace Aprilaire, Honeywell, Carrier, Bryant, Lennox, ICP, and others.

| | Nu-Calgon Number | ClenAir Number |
|---|------------------|----------------|
| Universal Humidifier Panel - #10 size | 61250 | CA10 |
| Universal Humidifier Panel - #12 size | 61251 | CA12 |
| Universal Humidifier Panel - #35 size | 61252 | CA35 |
| Ultra Upgrade Humidifier Panel - #10 size | 61254 | CA10UP |
| Ultra Upgrade Humidifier Panel - #35 size | 61255 | CA35UP |

Spacegard® Filter Media Replacements

These Merv 11 filter media are direct replacements for the Aprilaire Spacegard 201 and 401. Merv 11 media removes pollen, allergens, smoke, dust, dust mites, bacteria, spores, and pet dander. The large filter surface area provides for low resistance and longer filter life, more than 6 months!

| | Nu-Calgon Number | ClenAir Number |
|--|------------------|----------------|
| Replacement for Aprilaire Spacegard 201 | 61256 | CA201 |
| Replacement for Aprilaire Spacegard 401 | 61257 | CA401 |

*Aprilaire and Spacegard are registered trademarks of Research Products Corporation

Gas Leak Detectors



Cal-Blue® Plus Gas Leak Detector

Cal-Blue Plus is a complete gas leak detector with freeze protection to 5°F. Its high viscosity formula enables it to remain in contact with the applied surface for an extended period of time, allowing it to detect the smallest of leaks. The longest lasting bubbles in the industry! It is also non-corrosive to metal, and it will not affect ultraviolet or black lights. NSF registered.

| 6 ounce bottle with dauber | 4182-53 | |
|----------------------------|---------|-------|
| 1 quart spray bottle | 4182-24 | (NSF) |
| 1 gallon bottle | 4182-08 | |



Cal-Blue® LT Gas Leak Detector

The same high quality formulation as regular Cal-Blue Plus, but it has added freeze protection to -20°F. It is the ideal detector for geographical areas that may experience very cold temperatures. The longest lasting bubbles in the industry! NSF registered.

| 1 quart spray bottle | 4183-24 | (NSF) |
|----------------------|---------|-------|
| 1 gallon bottle | 4183-08 | M9Ľ |



Gas Leak Detector

The original industry leak detector. A high viscosity liquid that forms bubbles when daubed on a gas leak. Non-corrosive, non-staining, and harmless to skin. Detects any type of gas leak, such as air, compressed air, carbon dioxide, nitrogen, natural gas, and refrigerant gases. Freeze protection to -20°F. Six ounce plastic bottles have dauber in cap. USDA approved.

6 ounce bottle with dauber

4180-53



Fluorescent Gas Leak Detector

A fluorescent formulation that provides improved visibility and long lasting bubbles. It is non-corrosive to metals and is freeze protected to 5°F. Suitable for high and low temperature applications. Can be used for most refrigerants, natural gas and oxygen systems. USDA approved.

| 8 ounce bottle with dauber | 4184-53 |
|----------------------------|---------|
| 1 quart spray bottle | 4184-24 |
| 1 gallon bottle | 4184-08 |



AccuTrak[®] Ultrasonic Leak Detector

Model VPE - Now with touchprobe included. Patented technology detects the ultrasonic sound of a leak!

| | Nu-Calgon Number | ClenAir Number |
|------------------------------------|------------------|----------------|
| AccuTrak® Ultrasonic Leak Detector | 61307 | CAVPE |

Polyol Ester (POE) Lubricant



Emkarate® RL Lubricant

The Emkarate family of polyol ester refrigeration lubricants are designed specifically for use with HFC refrigerants. They are available in a range of viscosities. They have excellent thermal and chemical stability, and they are compatible with a wide range of elastomers, polymeric materials, and other materials of construction. Fully miscible and compatible with mineral oils and alkylbenzene lubricants as well as with CFCs, HCFCs and HFCs.

| Emkarate RL | Viscosity | 1 Quart | 1 Gallon | 5 Gallon | 53 Gallon |
|-------------|-----------|---------|----------|----------|-----------|
| 22H | 100 SUS | | 4313-46 | | |
| 32H | 150 SUS | 4314-44 | 4314-46 | 4314-45 | 4314-41 |
| 32HB | 150 SUS | | | 4314-62 | |
| 32-3MAF | 150 SUS | 4314-64 | 4314-66 | 4314-65 | 4314-67 |
| 46H | 200 SUS | | 4315-46 | | 4315-41 |
| 68H | 300 SUS | 4316-44 | 4316-46 | 4316-45 | 4316-41 |
| 68HB | 300 SUS | | 4316-86 | 4316-85 | |
| 68HP | 300 SUS | | 4316-76 | | 4316-71 |
| 100E | 500 SUS | | 4317-66 | | |
| 100H | 500 SUS | | 4317-46 | | |
| 170H | 850 SUS | | 4318-26 | 4318-25 | 4318-21 |
| 220H+ | 1100 SUS | | 4318-66 | 4318-65 | 4318-61 |
| 220XL | 1100 SUS | | | 4318-75 | |

Mineral Oil



C-3s, C-4s, C-5s Refrigeration Oil

These are mineral naphthenic lubricants manufactured by Calumet Lubricant Company and available in three viscosities. They are specifically designed for today's high performance air conditioning and refrigeration compressors using CFC and HCFC refrigerants. These compressors run at higher speeds and generate higher temperatures, and as a result, they require better lubrication. Use of these oils will ensure continued efficient operation.

| Nu-Calgon | Viscosity | 1 Gallon | 5 Gallon | 55 Gallon |
|-----------|-----------|----------|----------|-----------|
| C-3s | 150 SUS | 4303-07 | 4303-05 | 4303-01 |
| C-4s | 300 SUS | 4304-07 | 4304-05 | 4304-01 |
| C-5s | 500 SUS | 4305-07 | | 4305-01 |

Polyvinyl Ether (PVE) Lubricant



Idemitsu Polyvinyl Ether Lubricant

PVE lubricants provide for increased stability and lubrication. They do not hydrolyze in the presence of moisture, a very important feature in HVACR applications. Additionally, they are compatible with other refrigeration oils and process fluids. PVE lubricants also exhibit compatibility and performance with frequently used anti-wear additives.

| Idemitsu | Viscosity | 1 Quart |
|----------|-----------|---------|
| FVC32D | 32 SUS | 4319-14 |
| FVC68D | 68 SUS | 4319-24 |

Alkylbenzene Oil



Zerol® Alkylbenzene Refrigeration Oil

Zerol Refrigeration Oil is recommended for use in all refrigeration and air conditioning applications using CFC and HCFC refrigerants. It is highly recommended by refrigerant and compressor manufacturers for use with R-22 and other HCFC blends such as R-409A as it provides many distinct advantages: excellent miscibility, excellent thermal stability, and low temperature performance compatibility with mineral oils. It is the oil of choice for R-22 and R-502.

| Zerol | Viscosity | 1 Gallon | 5 Gallon | 55 Gallon |
|-------|-----------|----------|----------|-----------|
| 150 | 150 SUS | 4310-07 | | 4310-01 |
| 200TD | 200 SUS | 4308-07 | | 4308-01 |
| 300 | 300 SUS | 4311-07 | 4311-05 | 4311-01 |
| 400CA | 400 SUS | | 4311-65 | |
| 500 | 500 SUS | | 4312-05 | |

Vacuum Pump Oil



Refrigeration Oil Products

Vacuum Pump Oil

Nu-Calgon's Vacuum Pump Oil is a quality, high-grade lubricant that performs at the deepest vacuum. It has a very low vapor pressure, and it has excellent lubricity for complete surface protection. It contains no additives or detergents.

| 1 pint bottle | 4383-34 |
|-----------------|---------|
| 1 quart bottle | 4383-24 |
| 1 gallon bottle | 4383-07 |









Refrigeration Oil Charging Pump

An oil pump for charging refrigeration oil into a system, even while it's running. This pump can be used for 1 gallon, 2.5 gallon, and 5 gallon containers. Incorporates an automatic bleed valve that keeps pressure equalized inside the container and includes a tapered rubber adapter that fits all container openings without the need for additional adaptors.

1 each

4814-40

Total Lube Refrigeration Oil Test Kit

Have a professional lab analyze the oil to help detect potential problems such as metal wear or burnouts. The analysis will provide information on the oil's moisture, total acid number, viscosity, color, and spectrochemical analysis on 20 plus metals and compounds. Help prevent potential downtime, burnouts, and costly oil changes by incorporating regular testing of the refrigeration oil.

1 each 4996-0

Oil Refractometer

A precision optical instrument that allows for the rapid and accurate determination of the refractive index of oil solutions. It will specifically assist in determining the percent of residual oil remaining in a refrigeration system when converting it to a new refrigeration oil. Such retrofits require converting the mineral oil to a polyol ester (POE) or polyalkylene glycol (PAG), an alkylbenzene lubricant (Zerol[®]) to a POE, or a mineral oil to an alkylbenzene.

1 each

4815-0

CanVerter®

A hand-held pump used to remove or add oil to hermetic compressors. Easy to use; each stroke pumps 1 ounce of oil.

1 each

4814-0

Aerosol Coil Cleaners

Evap Foam No Rinse®

Evap Foam No Rinse is a high-performing, heavy-duty detergent. It is formulated with special surfactants and alkaline cleaners that have been developed into a foaming, no-rinse product. Evap Foam is ideal for use on most coils, but it is particularly suited for use on cooling or evaporator coils. The aerosol can be sprayed either right side up or upside down. NSF registered. **Can be used with the Talon Flexible Aerosol Wand** (4776-0) for hard to reach locations.

4171-75

NSF

18 ounce can



Talon Flexible aerosol wand for Nu-Calgon's Evap Foam No Rinse, Blackhawk or PenetrateHD products. Provides focused cleaner spray or penetrant in tough-to-reach locations. The Talon is highly flexible, retains shape memory, and provides 27 inches of added length to an aerosol canister for navigating in tight quarters inside the equipment. The reusable Talon is a must-have service tool!

4776-0

1 each



Nu-Brite®

Nu-Brite is a very effective degreaser and cleaner on condenser coils. Its high foaming characteristic will help push soil deposits out of the coil, leaving it clean and bright. With proper ventilation, it can also be used as a kitchen degreaser by emulsifying stubborn, resistive grease deposits found on coils located in kitchens. Product should be used where adequate rinsing is possible.

4291-18

18 ounce can

Evap-Fresh No Rinse

Evap-Fresh® No Rinse

Evap-Fresh is a ready-to-use, no-rinse cleaner and disinfectant for evaporator coils. It effectively cleans as well as kills mold and bacteria. This one-step no-rinse disinfectant cleaner is perfect for air conditioners, commercial air handling units, HVAC cooling coils, refrigeration equipment, and evaporator coils. EPA registered specifically for use on HVAC equipment.

18 ounce can

4166-75



Cal-Blast[®]

Cal-Blast is a no-rinse condenser cleaner that will powerfully separate undesirable materials from the surface, offering maximum cleaning of finned coils. It's a high-performance aerosol with excellent solvency and blasting spray.

20 ounce can 4132-20



Nu-Blast®

A no-rinse condenser coil cleaner in a convenient aerosol package. Double action of high-pressure blast and solvent cleaning restores design efficiency of condenser coils. It is non-flammable and non-conductive. No rinse required — cleaning solvent evaporates completely. Use with adequate ventilation.

18 ounce can

4290-75



Blackhawk®

Blackhawk is an expanding foam coil cleaner. Formulated to deeply penetrate the coil, it liquefies to quickly remove grease, grime, or oily soils from deep within the coil. Blackhawk's formulation is safe and problem-free for cleaning evaporator or condenser coils in an occupied building; produces no objectional fumes. It is particularly effective on coils on refrigerators, coolers, and freezers located in restaurants and other commercial establishments. NSF registered. **Can be used with the Talon Flexible Aerosol Wand (4776-0) for hard to reach locations.**

4127-75

18 ounce can



NSE

CalClean®

CalClean is a heavy-duty detergent formulation of surfactants, grease solvents, alkaline cleaners, corrosion inhibitors, and water conditioners. Ideal for cleaning window units as well as small evaporator coils, air-cooled condenser coils, metal filters, fan blades and other surfaces soiled with greasy dust and dirt. NSF registered.

| 20 ounce can | 4081-75 | (NSF.) |
|--------------|---------|--------|
| | | |



Nu-Shield®

Nu-Shield, the newest generation of chemistry for protecting coils and other surfaces, is a super-hydrophobic (water repelling) product. The non-conductive formula has numerous applications in the management of water on non-food, non-potable water surfaces for the HVACR trade. Simply spray it on and watch the water bead up and roll right off.

9 ounce can

4294-75



DuraCoil

DuraCoil is a long-lasting coating for coils and surfaces in corrosive environments. It uses a durable, OEM-approved Heresite® Coating. DuraCoil has a fast, air-dry formula that bonds to all metals and causes negligible heat transfer loss across the coil. Great for repairing an OEM-applied coil coating that has been compromised while in service! Brown in color.

11 ounce can

4083-90





A/C Shine[®] Superior Cleaner / Protectant

A/C Shine is specially formulated to clean and protect the painted metal surfaces of outdoor A/C condensing units. It sprays on and wipes off guickly and easily without water. For use on all outdoor unit painted surfaces.

| 1 | | Nu-Calgon Number | ClenAir Number |
|---|--------|------------------|----------------|
| | 12 oz. | 61118 | ACS12 |
| | | | |

lenAir

| - | |
|------|---|
| | - |
| Pan- | and the second se |
| | Pan Spra |
| - | |
| | A MARKED |
| 1 | |
| 100 | |
| | 100-1-122 |

Pan-Spray®

Pan-Spray is an effective, easy-to-use waterproof rubberized coating that won't chip, flake, or peel. It's ideal for sealing out rust and corrosion as well as repairing leaky condensate pans, cooling towers, swamp coolers, roofing, gutters, and down spouts. Pan Spray is the perfect solution for emergency and permanent repair.

| 16 ounce can - White | 4296-50 |
|----------------------|---------|
| 16 ounce can - Black | 4296-51 |
| | |

Aerosol Lubricants



Break-n-Lube[™]

This advanced technology 4-in-1 product is made with CERFLON® for high performance in a non-drying penetrating lubricant. It's highly versatile with the ability to penetrate, lubricate, displace moisture, and provide superior resistance to corrosion. It's specially formulated to help free rusted parts and assemblies.

4128-03

12 ounce can



Food-Grade Silicone

Food Grade Silicone sprays a perfect non-stick surface on ice machine surfaces, vending machines, coin slots, slicing machines, dairy machinery, and other food processing and packaging equipment. An excellent lubricant that prevents binding and sticking. Contains ingredients approved by the FDA for food contact use. USDA approved.

11 ounce can

4084-03



ClenAir

PenetrateHD® Super Penetrating Lubricant

Loosens rusted and frozen metal parts. Frees stuck fan blades, blower shafts, pulleys, rusted nuts and bolts, and any frozen, rusted, or seized metal part. Unique low surface tension formula penetrates into the smallest spaces and breaks and dissolves the bonds of rust and corrosion. Lubricates and protects metals. Dielectric strength 40,000 volts. Can be used with the Talon Flexible Aerosol Wand (4776-0) for hard to reach locations.

| | 12 ounce can | 61105 |
|-------|--------------------|-------|
| 1 | 17 ounce can | 61106 |
| | 12 ounce can - LV* | 61107 |
| algon | 17 ounce can - LV* | 61108 |
| | | |

* LV = Low VOC for California



V-Belt Dressing

V-Belt Dressing is specially formulated to penetrate and extend modern V-Belt life. It is particularly effective in maintaining V-Belt efficiency and performance under today's increasing performance requirements. It keeps belts pliable, prevents slippage, and does away with squealing and chattering. USDA approved.

11 ounce can

4086-03

Aerosol Adhesives

Spray-n-Bond[™]

A wide web spray adhesive formulated specifically for insulation and duct liner applications. Ideal for porous surfaces, it is waterproof, flexible, transparent, non-staining, and it can be used for both temporary or permanent bonds. Formulated with the environment in mind, it contains no chlorinated solvents or ozone depleters, and it is VOC-compliant in states such as California.

12 ounce can 4369-75



Spray Adhesive

Spray Adhesive is a fast-drying, all-purpose product that provides a strong, water-resistant, flexible bond. It is translucent and does not penetrate or soak material causing bleed-through. Spray Adhesive is excellent for labeling, bonding, splicing and sealing paper, cardboard, cloth, rubber, styrofoam, canvas, leather, wood, and most plastics.

| 1100 | 12 ounce | can |
|------|----------|-----|
| | | |

4080-04

Aerosol Specialty Products



Pipe-Dri®

Aerosol insulation that provides a moisture barrier to stop sweating and dripping on refrigeration lines, air conditioning lines, and other cold surfaces. Quickly adheres and dries to a hard waterproof coating. Pipe-Dri makes it possible to insulate hard-to-reach areas.

| 18 ounce can | 4297-75 |
|--------------|---------|
|--------------|---------|



Nu-Kill® II Wasp and Hornet Killer

A "quick-kill" spray formulation EPA registered to instantly and effectively kill wasps, hornets, and yellow jackets, from distances up to 20 feet. Nu-Kill II also kills with residual action as wasps and hornets return to a treated nest. The formula is safe in and around electrical equipment, having a dielectric strength of 47,000 volts.



4292-75



Pump Protector

When corrosion occurs in close-tolerance areas, it can cause the impeller to stick or bind. Pump Protector protects seasonally operated pumps against corrosion during shutdowns by winterizing them. It is safe for all types of water pumps and requires no special rinsing at start-up.

4299-T8

10 ounce can



Zinc Rich Cold Galvanizing

Highly resistant to nearly all forms of corrosion. Perfect for repairing factory galvanized material damaged in shipment, welding, assembly, etc. Its 95% pure zinc film fuses itself to iron, steel, or aluminum. Blends well with hot-dip coating. Meets or exceeds military specifications MIL-P- 26915A, MIL-T- 26433, MIL-P- 21035, MIL-P-46105 and the Preece Test.

13 ounce can

4087-03



Electrical Contact Cleaner

Cleans, lubricates, and protects electrical contacts from corrosion, and it is safe on most plastics. Cleaning action quickly removes greases, dust, and oxidation, restoring and maintaining precision and efficiency to the instrument and component. Includes extension tube for pinpointing application. USDA approved.

| 11 ounce can | 4082-03 |
|--|---------|
| 14 ounce can - LV * | 4082-04 |
| * LV = Low VOC for California and Canada | |



Degreasing Solvent EF

A degreasing solvent, specially formulated for cleaning and degreasing equipment where washing or flushing is not possible. Simply spray on and wipe off. Penetrates quick and deep, loosening and liquefying heavy greases and tar. Non-corrosive and non-staining with a dielectric strength over 26,000 volts.

| | 14 ounce can | 4083-75 | |
|---|------------------------------|---------|--|
| | 14 ounce can - LV* | 4083-83 | |
| - | * 11/ Low/VOC for California | | |

* LV = Low VOC for California

Specialty Products















Great Wipes

Great Wipes Industrial Strength Hand Towels are waterless wipes made specifically for the air conditioning, refrigeration, and plumbing service technician. Each premoistened, heavy duty towel has strong pumice scrubbing power that conveniently cleans anywhere and anytime.

75 count canister

4185-75

(NSF)

Scrubs-In-A-Bucket® HVAC80

The original Scrubs — disposable, pumice-performance waterless hand cleaner towels that effectively and quickly clean hands on a wide variety of industrial soils and greases. Each self-dispensing portable canister contains 80 perforated disposable heavy-duty towels and are pre-moistened with the famous Scrubs cleaning formulation. Effective yet gentle to the skin. Use anywhere, anyplace, anytime.

| 30 count canister | 4366-24 | NCE |
|-------------------|---------|-----|
| 80 count canister | 4366-87 | MOL |

Quick Seal[™] Pipe Repair

A permanent knitted fiberglass impregnated tape that is designed for quick, in-the-field repair of leaks for all types of pipes. It can be used on both cold or hot water as well as refrigeration, plumbing, industrial, commercial, and residential applications. It is safe for potable water and is UL listed. ANSI/NSF Standard 61.

| 2″ x 3´ wrap | 4299-10 |
|---------------|---------|
| 4″ x 12′ wrap | 4299-11 |

Pneu-flush®

A flushing and cleaning system specifically designed for pneumatic control air lines. It utilizes DuPont[®] Vertrel[®] XM, a premier ozone-safe HFC cleaning solvent. Pneu-Flush works quickly and easily to clean and purge the compressed air lines in HVAC control and other pneumatic systems.

| 2 lb. canister | 4298-01 |
|-----------------|---------|
| Injection Valve | 4300-89 |

(Injection Valve fits R_X11-flush[®] and Pressurized Rx-Acid Scavenger[®] as well)

Thermo-Trap®

The industry's original heat absorbing paste designed to isolate heat encountered in soldering, welding, and brazing, thereby preventing damage to nearby heat sensitive controls, or fittings. USDA approved. Biodegradable. Available in paste or gel.

| Thermo-Trap paste | 11 ounce tube | 4371-36 |
|-------------------|----------------------------|---------|
| Thermo-Trap gel | 1 quart spray bottle | 4371-32 |
| Thermo-Trap gel | 4 fluid ounce spray bottle | 4371-53 |

Degreasing Solvent EF

Degreasing Solvent EF is a volatile solvent, especially formulated to provide effective cleaning and drying and reduce safety hazards. It leaves surfaces clean and oil-free. The thorough cleaning action is superior to ordinary chlorinated solvents.

| 1 gallon | 4162-07 |
|----------------|---------|
| 1 gallon - LV* | 4162-17 |

* LV = Low VOC for California

Visible Defects Heat Exchanger Inspection System

The Visible Defects Heat Exchanger Inspection System is a complete kit that enables the technician to better evaluate the integrity of a heat exchanger. If a crack exists, the specially formulated fluorescent penetrant visually enhances the crack, allowing the technician to see the defect easier.

| Visible Defects kit | 4385-00 |
|-----------------------------------|---------|
| Crack Finder replacement solution | 4385-06 |

General Purpose Cleaners





Green Clean

A pleasantly scented, all-purpose, environmentally friendly cleaner designed for the rapid removal of grease and other heavy soils. It can be used right out of the bottle or diluted for milder jobs. Biodegradable. Also great for microchannel coils.

| 1 quart spray bottle | 4186-24 |
|----------------------|---------|
| 1 gallon bottle | 4186-08 |
| 55 gallon drum | 4186-01 |

Spray Nine® Cleaner & Disinfectant

Spray Nine is a tough task cleaner and broad spectrum disinfectant. EPA-registered Disinfectant kills harmful germs like HIV-1, Influenza, H1N1, Staphylococcus Aureus, Salmonella Choleraesuis and E. Coli in 45 seconds. Also helps prevent cross contamination. Authorized by USDA for use in federally inspected meat and poultry plants with a C-1 rating.

| | Nu-Calgon Number | ClenAir Number |
|--------------|------------------|----------------|
| 1 gallon | 61110 | 26801 |
| 32 oz. spray | 61113 | 26832 |

Grez-Off® Heavy Duty Degreaser

Grez-Off works hard so you don't have to. This heavy-duty answer to heavy-duty grease and grime leaves engines, machinery, asphalt, garage floors and more whistle clean. Biodegradable, non-flammable formula hits hard and fast with less impact on user and environment.

| | | Nu-Calgon Number | ClenAir Number |
|---------------|--------------|------------------|----------------|
| | 1 gallon | 61116 | 22701 |
| en Air | 32 oz. spray | 61117 | 23732 |
| Nu-Cålgon | | | |

Other Specialty Products



Elite® Performance Windshield Washer Cleaner -20°

Elite Performance Windshield Washer is independently tested to provide freeze protection to -20°F. Don't take chances with generic washer products; only Elite Performance offers certified protection.

| | Nu-Calgon Number | ClenAir Number |
|----------|------------------|----------------|
| 1 gallon | 61115 | CAWW1G |

ClenHands: Orange Smoothie[™], Orange Crush[™] and Cherry Crush[™]

Premium antimicrobial hand cleaners that quickly dissolve dirt, grease, fuel oil, pipe dope, resin, ink, paint, glue, rubber gasket and tile cements and many other hard-to-remove soils. ClenHands Orange Smoothie is a smooth non-pumice formula, while ClenHands Orange Crush is enhanced with fine-ground American pumice. ClenHands Cherry Crush is a cherry-scented antimicrobial hand cleaner with pumice. For use with or without water.

| | | Nu-Calgon Number | ClenAir Number |
|----------------------------|----------|------------------|----------------|
| Orange Crush with Pumice | 1 gallon | 61201 | 2201 |
| Orange Smoothie Non Pumice | 15 ounce | 61202 | 2202 |
| Orange Crush with Pumice | 15 ounce | 61203 | 2215 |
| Cherry Crush with Pumice | 15 ounce | 61204 | 2315 |
| ClenHands Super Gel | 11 ounce | 61205 | 2414 |



Smoke Signal[™] Smoke Candles and Smoke Pens

Smoke Signal generates smoke by chemical reaction, eliminating costly equipment and time to pinpoint leaks. Smoke tests will effectively and inexpensively reveal leaks in heating and air conditioning duct work, furnaces, fire boxes, exhaust fans and smoke detectors. Smoke Pens are also excellent for observing ventilation, air balancing, smoke detectors, drafts, leakage, and air flow. The Smoke Pens come with one pen, six replacement wicks (refills available) and instructions. Smoke Signal items contain no explosive materials.

| | Nu-Calgon Number | ClenAir Number |
|--|------------------|----------------|
| Smoke Candle - 4000 cubic feet of smoke 30 sec 1A | 61302 | CAS30 |
| Smoke Candle - 8000 cubic feet of smoke 60 sec 2B | 61303 | CAS60 |
| Smoke Candle - 40,000 cubic feet of smoke 2-3 min 3C | 61304 | CAS180 |
| Smoke Pen | 61305 | CASP1 |
| Refill Package - 6 wicks | 61306 | CASP1RW |



Insulation Products



Perma-Wrap™

Foam Insulation Tape

Formulated from the highest quality elastomeric thermal insulation material. Its closed cell construction seals out air and moisture, slowing down heat transfer, and can be used on hot or cold water pipes, chilled water, and refrigerant lines to prevent sweating and condensation. Service temps as low as -20°F with a high continuous temperature of 160°F and a high intermittent temperature of 220°F.

| 2″ x 1/8″ x 30′ roll | 4218-W3 |
|------------------------|---------|
| 2″ x 1/8″ x 30′ roll - | 4218-12 |
| dispenser package | |



Cork Tape

Formulated and manufactured as an insulating material for preventing sweating and condensation on refrigerant lines, cold pipes, and other commercial refrigeration and A/C systems. Serves as an excellent insulator on hot pipes, and can also be used as a gasketing material, a sound-deadening material, and for wrapping valves, tees, and fittings. Service at temps as low as -30°F, as high as 200°F and won't sag up to 350°F.

2" x 1/8" x 30' roll 4217-W3



Foam-Tite®

An economically priced tape formulated from quality thermal insulation material. Closed cell construction and can be used on cold water pipes, chilled water lines and refrigerant lines to prevent sweating and condensation. It can also be used on hot water lines, for better insulation against heat loss. Service temperatures of -15°F to 160°F.

2" x 1/8" x 30' roll 4219-12



Cork-Tite®

Designed to insulate cold pipes for all kinds of air conditioners in cars, homes, freezers, and refrigerators. Helps stop condensation problems and is ideal for blocking heat gain in cold pipes and preventing heat loss in hot pipes. An effective sound dampening material, it can also be used for gasketing purposes, sticks to dry metals and seals tightly without drying. Flexible and does not shrink or melt within the service temperatures of -20°F to +200°F.

2" x 1/8" x 30' roll 4217-12



Foam Tape PE

Insulation tape providing an economical way to prevent sweating or condensation on air conditioning, refrigeration, chilled water or other cold lines. Also used on hot water lines for insulation against heat loss, and it can be overlapped or the edges can be pressed together.

2" x 1/8" x 30' roll 4219-20



Thumb-Tite®

Formulated and manufactured for use in many sealing, insulating, and general maintenance applications. Excellent adhesion capability and is non-staining, non-hardening, and unaffected by wide variations in temperature — an excellent thumbing grade. Each box contains two 1-pound bars.

2 lb. box

4216-92



Nu-Foam®

An expanding polyurethane prepolymer foam used as a sealant and insulating product on openings created for refrigeration, air conditioning and heating tubes or pipes, duct joints, and other areas where unwanted air penetration might occur. Contains no CFCs or any HCFCs and is UL classified and fire retardant.

| 12 ounce can | 4293-04 |
|--------------|---------|
| 20 ounce can | 4293-75 |
| | |



Sealing and Caulking Cords

Nonstaining sealers formulated to be waterresistant, dust- resistant and white in color. They securely adhere to most surfaces and provide excellent insulation value. They are available in 3/8" pre-shaped extruded cords, with serrated release paper.

3/8[°] x 25[°] roll 4216-27







Ethylene Glycol

Freez-Kontr'l 35

Freez-Kontr'l FG



Glycol Equipment







Freez-Therm®

5 gallon pail

Burst-Kontr'l® AP-100

An inhibited heat transfer fluid and anti-freeze based upon ethylene glycol. It can be used in chilled water, hydronic, and other closed systems for both freeze point suppression and corrosion inhibition. An uninhibited version is also available in drums on special order.

A specially formulated propylene glycol heat transfer solution for use in boilers having aluminum heat exchangers. It has corrosion inhibitors to protect aluminum, copper, solder, brass, and steel. Provides burst protection to -100°F and freeze protection to -60°F.

4187-15

(NSF)

| 1 gallon bottle | 4189-07 |
|-----------------|---------|
| 5 gallon pail | 4189-05 |
| 55 gallon drum | 4189-01 |

Glycol Refractometer

An accurate and economical tool for ensuring proper levels of glycol treatment in HVAC fluid systems. Removes guess work and prevents wasteful over-treatment. It has metal body with cushioned eyepiece, focus adjustment, and a rubber hand grip. A calibration screwdriver, calibration fluid, a plastic pipette, optical cleaning cloth, and a rugged carrying case are included.

| | Nu-Calgon Number | ClenAir Number |
|--------|------------------|----------------|
| 1 each | 61301 | GLY32 |

Glycol/Oil Transfer Pump

Heavy-duty pump designed to transfer Freez-Kontr'l®, Freez-Therm®, or oil products (up to 1000 sus) from Nu-Calgon supplied 55 gallon drums to their application.

| 1 each | 4817-0 |
|--------|--------|
|--------|--------|

Closed Systems & Steam Boilers









Water Test Kits

Bacteria Test Kit

Kit contains 10 agar paddle tests that are used to monitor bacterial
contamination in cooling tower and evaporative condenser water. Test
can be performed in a lab or on site. Each side of the paddle is coated
with TTC Agar, material that supports growth of most common bacteria.
Regular testing will detect and show when bacteria counts are rising.1 each4802-0

| eaci | 1 |
|----------|---|
| | |

Complete Test Kit

The complete test kit for cooling water and boiler water application testing. In addition to pH, this kit also provides tests for obtaining alkalinity, nitrite, hardness, sulfite, and chloride levels.

| 1 each | W017-0 |
|--------|--------|
|--------|--------|

No. 89A Test Kit

No. 89A Test Kit contains tests for determining hardness, pH, chloride and alkalinity, as well as treatment residual tests for Ty-Ion C70, Cal-Treat 233, No. 340 Liquid Scale Inhibitor, and Ty-Ion B20.

4798-2

1 each

Winter Treat®

Multi-treatment product for hot water and steam heating boilers and other closed water systems. It emulsifies and cleans away rust and corrosion deposit sludge, as well as inhibits system corrosion, foaming, surging, and lime scale. Typical use is one quart per 25 gallons of water.

| 1 quart bottle | 4390-32 |
|-----------------|---------|
| 1 gallon bottle | 4390-08 |

Ty-lon[®] B20

A liquid nitrite-borax corrosion inhibitor and dispersant for closed recirculating systems. It combines corrosion inhibitors, a unique copolymer dispersant, and a color indicator to facilitate leak detection, into a complete treatment for hot and chilled water closed systems containing ferrous and non-ferrous metal components.

| 5 gallon pail | 7537-05 |
|---------------|---------|
| | |

Ty-lon[®] B14A

An all-in-one boiler treatment product that controls scale, corrosion, and condensate line corrosion in low pressure, low make-up steam heating boilers where 90% or more of the condensate is returned. It is chromate-free and contains a color indicator for visual determination of treatment residual. Its balanced formulation provides an energy-efficient way of heating.

| 5 gallon pail 7519-05 |
|-----------------------|
|-----------------------|

System Cleaner

A liquid, heavy-duty industrial alkaline cleaner specifically formulated to emulsify and clean equipment surfaces and pipe fouled by cutting oils, grease, lubricants, corrosion products, and other debris.

5 gallon pail

4370-08

Bromine/Chlorine Test Kit

Kit measures free and combined halogen (chlorine, bromine), and it should be used to support treatment with Bromicide Tablets. Residual can be expressed as 0.2 ppm or 0.5 ppm of free halogens. Dropper technique is used.

1 each 4803-0

Nitrite Test Kit

Used for testing treatment residual of Ty-Ion B20 and Ty-Ion B14A. It is a cerric ammonium nitrate (can) titration method, and it can be used in systems containing glycol. Each drop equals 40 ppm of nitrite.

| 1 each | 4797-0 |
|--------|--------|
|--------|--------|

Organic Phosphonate Test Kit

Used to determine the treatment residual of No. 340 Liquid Scale Inhibitor, Ty-Ion C70, and Cal-Treat 233.

1 each 4804-0

Visit us at www.nucalgon.com or call 1-800-554-5499

Scale Removal



Liquid Scale Dissolver

A hydrochloric (muriatic) acid formulated to remove calcium scales from cooling towers and other water-cooled equipment. It contains low-foaming corrosion inhibitors and a built-in pH color indicator to let you know when the acid has been neutralized. pH test paper is also included. USDA approved.

| 1 gallon bottle | 4330-08 |
|-----------------|---------|
| 5 gallon pail | 4330-05 |
| 55 gallon drum | 4330-01 |



Eco-Lyme[®]

Eco-Lyme is a new chemistry for the HVACR market that provides a unique blend of performance with a desired eco-profile. The product is specially formulated to achieve descaling behavior of competing hydrochloric acid-based chemistry descalers. However, the active ingredient is substantially safer on equipment metals. Eco-Lyme is ideal for stainless steel construction to eliminate potential issues of localized corrosion/pitting caused by repeated use of hydrochloric acid. Eco-Lyme is odorless, making it safer to use in the field. NSF registered.

| 1 gallon bottle | 4167-08 | \frown |
|-----------------|---------|----------|
| 5 gallon pail | 4167-05 | (NSF) |
| 55 gallon drum | 4167-01 | |



Season Start® "Imperial Grade" Scale Remover

A powdered sulfamic acid formulation that contains the best inhibitors available for protecting all metals, including galvanized metal. It is the best and the safest dry acid cleaner available. It contains a built-in pH color indicator to let you know when the acid solution has been neutralized as well as wetting and anti-foaming agents. USDA approved.

| 10 lb. container | 4360-88 |
|------------------|---------|
| 50 lb. pail | 4360-84 |

| Initial Dosage Recommendation | | | |
|-------------------------------|------------------------|------------|--------------|
| Tons of Horsepower | Liquid Scale Dissolver | Eco-Lyme | Season Start |
| 10 | 2 gallons | 4 gallons | 10 lbs. |
| 30 | 5 gallons | 10 gallons | 30 lbs. |
| 50 | 10 gallons | 20 gallons | 50 lbs. |
| 90 | 15 gallons | 30 gallons | 75 lbs. |

Water Heater Scale Removal



Feeding Equipment





Scale Prevention







Vital-Flo® Tankless Water Heater Descaler Kit

The Vital-Flo Tankless Water Heater Descaler Kit is a complete service tool for descaling tankless water heaters. It consists of a submersible descaler pump, a set of 5-foot long hoses with 3/4["] female hose threaded assemblies, formulated descaler solution packaged in a lidded 4 gallon chemical resistant container. The solution is also available separately. NSF registered.

| Vital-Flo kit | 4387-01 | NCE |
|-----------------------------|---------|-----|
| Vital-Flo descaler solution | 4387-02 | MOL |

No. 31-TX1 Acid Pump

Compact submersible pump designed for circulating strong acids and cleaning solutions. All parts are constructed of acid-resistant materials.

HK-31 Hose Kit

An accessory item available for use with the No. 31-TX Acid Pump. Kit includes two 1/2 inch tubing adapters, two 10 foot sections of 1/2 inch clear plastic tubing and three hose clamps.

| | 1 each | 4604-0 |
|--|--------|--------|
|--|--------|--------|

Season Treat (6R Micromet®)

This patented Micromet[®] Plate product is contained in a unique flow-through package. The package design makes it simple to treat small cooling towers and evaporative condensers. Simply unwrap the package and place it in the sump. One canister treats up to 10 tons for scale (5 tons for corrosion) for five to six months.

| 1 | 1261 00 |
|------------|---------|
| l canister | 4364-88 |

Ty-lon[®] C70

An all-organic liquid scale, deposit, and corrosion inhibitor for use in open recirculating cooling water systems, evaporative condensers, and air washer systems. This treatment program is particularly effective in preventing scale deposits in systems that utilize make-up water with high scaling potentials.

| 5 gallon pail | 7597-05 |
|----------------|---------|
| 15 gallon pail | 7597-P3 |
| 55 gallon drum | 7597-01 |

No. 340 Liquid Scale Inhibitor

An extremely concentrated scale inhibitor that is effective in hard, highly alkaline water. It is very stable and does not form any sludge. It is most effective at treatment levels between 10 and 15 parts per million. A constant, accurate feed is accomplished with a Drip Feeder or CMS Feed Pump. USDA approved.

| 1 gallon bottle | 4340-08 |
|-----------------|---------|
| 5 gallon pail | 4340-05 |
| 55 gallon drum | 4340-01 |

| | | To Inhibit Scale Formatio | on | |
|--|-------------------------------|----------------------------------|--|--|
| Tons of Refrigeration or Horsepower | Containers of Season Treat | Ty-lon C70 Required per Month | No. 340 Liquid Scale Inhibitor Required per Month | Bleed-off for Most Scale-forming Waters |
| 10 | 1 | 1/4 gallon | 1/4 gallon | 1/8 gpm |
| 30 | 3 | 2/3 gallon | 1/2 gallon | 1/3 gpm |
| 50 | 5 | 1 gallon | 3/4 gallon | 1/2 gpm |
| 100 | | 2 gallons | 1 1/2 gallons | 1 gpm |
| 120 | | 2 1/2 gallons | 2 gallons | 1 1/4 gpm |
| 150 | | 3 gallons | 2 1/2 gallons | 1 1/2 gpm |

Corrosion Prevention



Californi No. 11

Cal-Treat® No. 233

A liquid formulation that is used for controlling severe corrosion in evaporative condensers and cooling tower systems. It is based upon a synergistic formulation of zinc, molybdate, and organic phosphonate. Provides superior corrosion control and inhibits scale accumulation.

5 gallon pail 4149-05

| To Control Corrosion | | | |
|--------------------------------------|-------------------------------------|--|--|
| Cal-Treat No. 233 Required per Month | Bleed-off for Most Corrosive Waters | Capacity of System in Tons of Horsepower | |
| 1/3 gallon | 1/10 gpm | 10 | |
| 1 gallon | 1/4 gpm | 30 | |
| 2 gallons | 3/8 gpm | 50 | |
| 3 gallons | 1/2 gpm | 90 | |

Algae Prevention



No. 85 Algaecide

No. 85 Algaecide is a polymeric, cationic biocide that has been developed for controlling biological growth in equipment. It is an EPA registered product to kill algae, bacteria, and fungi in recirculating water systems, industrial air washing systems, and closed systems.

| 1 gallon bottle | 4108-08 | |
|-----------------|---------|--|
|-----------------|---------|--|



Bromicide Tablets

A chlorine-bromine donating organic compound in tablet form. It slowly releases powerful oxidizing hypohalous acids, which prevent algae and slime bacteria fouling in open recirculating cooling water systems and evaporative coolers. It also has the capability of breaking up and removing existing biological mass from system surfaces. USDA approved and EPA registered.

| 50 lb. pail | 4109-M9 | |
|-------------|---------|--|
| 50 lb. pail | 4109-M9 | |

| To Kill Algae or Slime Growth | | | | |
|---|------------|---|--|--|
| Tons of Refrigeration or Horsepower Gallons of No. 85 Algaecide per Month | | Number of No. 90 Bromicide Tablets for an Average System | | |
| 10 | 1/6 gallon | 5 | | |
| 30 | 1/3 gallon | 15 | | |
| 50 | 1/2 gallon | 25 | | |
| 90 | 2/3 gallon | 45 | | |

Other Water Treatment Products



Humidi-Pro™

Humidi-Pro is designed for humidifiers using up to 25 gallons per day and will inhibit scale for one season. Install Humidi-Pro on the water line that supplies water directly to the humidifier.

| 190-02 |
|--------|
| 1 |



pH-Treat[™]

pH-Treat is an in-line treatment product specifically for the treatment of the acidic nature of the condensate water produced by today's high efficiency furnaces. Includes fitting kit for easy installation.

1 each

```
4720-06
```

Other Water Treatment Products













Evap-Treat®

Used in evaporative coolers or "swamp coolers" to prevent scale and corrosion. Place it in the cooler sump and it will last all season long, thereby increasing pad life. Utilizes 6R Micromet[®], a slow dissolving polyphosphate.

| 1 each (coolers up to 6,500 cfm) | 4173-04 |
|-----------------------------------|---------|
| 1 each (coolers up to 10,000 cfm) | 4173-06 |

Water Sample Bottles

The proper way to treat a cooling tower, closed loop system, or ice machine is to have the supply or makeup water tested. Nu-Calgon provides this valuable service for free and will analyze the water and recommend effective treatment. These bottles can also be used to send in glycol samples to test freeze points.

| 1 each (3 bottles) | 4995-0 |
|--------------------|--------|
|--------------------|--------|

No. 215 and No. 1075 Drip Feeders

Used for feeding No. 340 Liquid Scale Inhibitor, Cal-Treat 233, Ty-Ion C70 and No. 85 Algaecide. Calibrated at the factory to ensure accurate feeding. Provides the benefits of continuous treatment for small systems without the high cost usually associated with automatic feeding equipment.

| No. 215 Drip Feeder | 4669-W3 |
|----------------------|---------|
| No. 1075 Drip Feeder | 4670-W3 |

Jug Holders

These should be used when drip feeding any of Nu-Calgon's liquid water treatment products. Once secured to the cooling tower or evaporative condenser, they will hold the 1 or 5 gallon containers in the proper position.

| 1 gallon holder | 4606-0 |
|-----------------|--------|
| 5 gallon holder | 4607-0 |

CMS III and CMS-IV Cooling Tower Monitor System

For monitoring conditions in cooling towers and evaporative condensers. Provides subsequent bleed-off and chemical feed. It features a combination monitor and pump engineered into one-piece digital equipment. Complete system includes a solenoid valve.

| CMS III | 4608-0 |
|---------|--------|
| CMS IV | 4608-4 |



No. 20L and No. 100L Feeders

Steel tanks suitable for pressures up to 150 psi and temperatures up to 212°F. Uses 3/4 inch FNPT connections for installing on bypass to any size line. Use No. 20L Feeder for initial charges up to 20 pounds (or 2 gallons). Use No. 100L Feeder for initial charges up to 100 pounds (or 10 gallons). Inlet/outlet strainers not included.

| No. 20L Feeder | 4628-0 |
|-----------------|--------|
| No. 100L Feeder | 4650-0 |



Conductivity Meter

A handheld conductivity meter with built-in cell and automatic temperature compensation. It has an easy-to-read digital meter (in micromhos, 0-10,000) and dual point calibrations.

1 each

4812-0

Plumbing Products



Drain Solve

Ideal for condensate pan drains. Drain Solve saves time and money with its ease of use. It eliminates application concerns associated with more reactive, fuming drain openers. Simply pour it down the drain and let it work without fear of noxious fumes or reactions. Does not contain sulfuric acid.

| 1 quart | 4165-24 | NSE |
|----------|---------|-----|
| 1 gallon | 4165-08 | NDE |









Calci-Solve

Remove scale from lines and clear clogged drains easily and effectively with Calci-Solve. The product includes a special inhibitor that coats the inside of the pipes with a protective film, allowing the acid in Calci-Solve to quickly dissolve calcium, magnesium, sodium, lime, rust, and other elements without harming pipes.

| 1 quart | 4134-24 |
|----------|---------|
| 1 gallon | 4134-08 |

UrinaKleen

Keep urinals free flowing with UrinaKleen. Use it to dissolve urinary salts, mineral scale, and rust deposits which are found in urinals. It also attacks the primary source of odors.

| 1 quart | 4590-24 |
|----------|---------|
| 1 gallon | 4590-08 |

A/C Drain Sucker®

A/C condensate drain pan overflow is caused by slime and sludge that builds up and clogs the drain line. The A/C Drain Sucker quickly removes the clog and the excess water, resolving the overflow problem. The kit includes a PurCool[®] Pan Strip to provide months of preventive treatment and free flowing drains, as well as all fittings and hoses for suction or pressure applications.

| | Nu-Calgon Number | ClenAir Number |
|--|------------------|----------------|
| A/C Drain Sucker kit | 61308 | CADS1 |
| PurCool Pan Strip - treats 3 tons - 6 mos. | 61043 | 1903D |

Vital-Flo® Tankless Water Heater Descaler Kit

The Vital-Flo Tankless Water Heater Descaler Kit is a complete service tool for descaling tankless water heaters. It consists of a submersible descaler pump, a set of 5-foot long hoses with 3/4" female hose threaded assemblies, and a formulated descaler solution packaged in a lidded four gallon chemical resistant container. The solution is also available separately. NSF registered.

| Vital-Flo kit | 4387-01 | (NSF) |
|-----------------------------|---------|-------|
| Vital-Flo descaler solution | 4387-02 | NOF |

Water Filtration - Maintenance



Nickel-Safe Ice Machine Cleaner

The original Nickel-Safe Ice Machine Cleaner. It is a food-grade citric-phosphoric acid product for removing scale deposits from ice machines having nickel-plated or tinplated evaporators, and it is acceptable for use in all ice machines containing nickel. It mixes to form a green solution, which makes rinsing easier. USDA approved.

| 16 fluid ounce bottle | 4287-34 |
|-----------------------|---------|
| 1 gallon bottle | 4287-08 |



Liquid Ice Machine Cleaner

Liquid Ice Machine Cleaner is a food-grade phosphoric acid that is fast acting, yet safe to use. It has been formulated to remove scale deposits from ice machines and coffee urns. It does not give off any harsh fumes or contain chlorine or chlorides that would attack stainless steel. USDA approved. NSF registered.

| 8 fluid ounce bottle | 4207-47 | (NSF) |
|----------------------|---------|-------|
| 1 gallon bottle | 4207-08 | Mar |

IMS-III Sanitizing Concentrate

IMS-III is an EPA registered sanitizing concentrate formulated to sanitize hard, non-porous surfaces and to eliminate odors and slime growths. No rinsing is required when diluted to 1.6 ounces per gallon. Formulated for general use in ice machines, ice cream dispensing equipment, and other food processing equipment.

| 16 fluid ounce bottle | 4211-34 |
|-----------------------|---------|
|-----------------------|---------|



Ice Guard[™] Plus

Ice Guard Plus contains advanced technology to prevent and control slime and other microbial growths in ice machines. The technology utilizes known antimicrobial properties to inhibit microorganism reproduction that cause slime typically found in ice machines. One unit provides up to 6 months protection in machines producing up to 1200 lbs. of ice per day.

| 1 each | 4209-07 |
|--------|---------|
|--------|---------|



6Rsp Micromet®

A slow dissolving phosphate specifically formulated for inhibiting scale in ice machines and other equipment using low volumes of water. It is used in Nu-Calgon scale controlling cartridges and requires replacement once every six months. Typical dosage is 8 ounces per 500 pounds of ice (50 gallons of water) a day.

4265-50

50 lb. pail

NSF)

Water Filtration - OEM Replacements



CFS Filtration System

A family of replacement cartridges and manifolds designed to service existing CUNO® CFS installations.

A cost-effective water filtration system for food service applications: ice machines, fountain beverages, steam ovens, and drinking water. These systems offer manifold and sanitary quick-change cartridges to fit the existing CUNO CFS brand installations and can also support new filtration installations. Nu-Plus CFS is the reliable choice for water filtration to prevent unwanted troubles caused by sediment, scale, or taste and odor existing in CUNO installations.

| Sediment – 5 micron | 4623-10 | Single Head | 4623-01 |
|----------------------------------|---------|-------------|---------|
| Sediment – 5 micron / phosphate | 4623-11 | Twin Head | 4623-02 |
| Carbon Block5 micron | 4623-12 | Triple Head | 4623-03 |
| Carbon Block5 micron / phosphate | 4623-13 | Twin Series | 4623-06 |



The CTL Series

The CTL Series contains a matching product for the Tri-Liminator Filtration System with specifications that are nearly identical. For example, the CTL's primary cartridge (C0070) will replace both the K00070 and K00174 cartridges, and it has more scale control ability than either of the Tri-Liminator cartridges. Part numbers are easily crossed over: CTL10 replaces the Tri-L10.

| CTL 220 | 4610-30 |
|-----------------------------|---------|
| Prefilter | 4621-43 |
| Primary cartridge - CG5-20S | 9108-27 |

Water Filtration



Micro-Plus® & Micro-Carbon 4

The complete all-in-one treatment for ice machines, coffee urns and brewers, humidifiers, steamers, etc. The Micro-Plus "in-line" filters contain 6R Micromet[®] to control scale, high-grade activated carbon for eliminating objectionable tastes and odors, and filter discs to remove silt and sediment down to 20 microns. Available in four sizes with 1/4" FPT connections. When properly sized, each filter will last up to six months. The Micro-Carbon 4 is available for removing objectionable tastes and odors.

| Micro-Plus 2 | 4615-W3 |
|----------------|---------|
| Micro-Plus 4 | 4612-W3 |
| Micro-Plus 8 | 4613-Y8 |
| Micro-Plus 16 | 4614-Y8 |
| Micro-Carbon 4 | 4617-24 |

| Application | Micro-Plus 2 | Micro-Plus 4 | Micro-Plus 8 | Micro-Plus 16 | Micro-Carbon 4 |
|-------------------|---------------------|----------------------|-----------------------|------------------------|----------------|
| Water (per day) | 12.5 gallons | 25 gallons | 50 gallons | 100 gallons | 50 gallons |
| lce (per day) | Up to 125 lbs. | Up to 250 lbs. | Up to 500 lbs. | Up to 1000 lbs. | |
| Coffee (per week) | 25 lbs.(1,250 cups) | 50 lbs. (2,500 cups) | 100 lbs. (5,000 cups) | 200 lbs. (10,000 cups) | |

Water Filtration - NP Series















NP Series Housings

These housings are designed to hold one of the NP Cartridges used to filter water for ice machines, coffee urns, and other beverage equipment. The NP24DD and NP48DD Housings fit specific NP24 or NP48 cartridges for controlling scale, sediment, or objectionable tastes and odors. The NP24DD is equipped with 3/8" FPT connections and handles up to 4.0 gpm. The NP48DD is equipped with 1/2" FPT connections and can handle flow rates up to 5.0 gpm.

| NP24DD | 4704-24 |
|--------|---------|
| NP48DD | 4714-24 |

6R Micromet[®]/Carbon Cartridge

A custom cartridge, combining 6R Micromet for scale-control and a carbon block for sediment (10 microns), taste and odor control.

| NP24PC | 4706-87 |
|--------|---------|
| NP48PC | 4716-87 |

Carbon Block Cartridge

The NP24C Cartridge fits the NP24DD Housing while the NP48C fits the NP48DD. These carbon blocks will remove most objectionable tastes and odors and are rated to remove particulate to 10 microns.

| NP24C | 4701-87 |
|-------|---------|
| NP48C | 4711-87 |

Sediment Cartridge

The NP24S (5") and the NP48S (10") are made from FDA-approved polypropylene construction and filter to 5 microns. In addition, the 10" and 20" versions are available in bulk packaging.

| NP24S | 4702-87 |
|----------------------|---------|
| NP48S | 4712-87 |
| 20 [″] bulk | 4621-43 |

6R Micromet® Cartridge

The NP246R Micromet Cartridge contains 1 pound of 6R Micromet, and it fits the NP24DD Housing. The NP486R Cartridge contains 2 pounds of 6R and fits the NP48DD Housing, with 10 micron filtration.

| NP246R | 4705-87 |
|--------|---------|
| NP486R | 4715-87 |

6R Micromet®/Sediment Cartridge

Another custom cartridge within the NP Series, consisting of polypropylene for filtration (5 microns) and phosphate for scale-control.

| NP48PS | 4717-87 |
|--------|---------|
| | ^ |

NP Series Brackets

Some installations may require two or three NP Series housings to meet more than one specific water-related condition. This custom installation can be accomplished through the use of one of the NP Series multi-housing brackets.

| Two housing brackets | NP2BR |
|------------------------|-------|
| Three housing brackets | NP3BR |

| Problem to Solve | | | Daily Ca | pacities | |
|------------------|-----------------------|-----------------------|-----------------------|----------------------|----------------------|
| Cartridge Type | Sediment | Taste & Odor | Scale | "24's" | "48's" |
| "S" Cartridges | V | | | 1800 lbs. (200 gal.) | 3600 lbs. (400 gal.) |
| "C" Cartridges | ✓ | ✓ | | 1800 lbs. (200 gal.) | 3600 lbs. (400 gal.) |
| "6R" Cartridges | v | | ✓ | 900 lbs. (100 gal.) | 1800 lbs. (200 gal.) |
| "PC" Cartridges | V | ✓ | ✓ | 600 lbs. (65 gal.) | 1200 lbs. (135 gal.) |
| "PS" Cartridges | v | | ✓ | | 550 lbs. (60 gal.) |



NU-PLUS **EVERPICE**



Heads



QL3B Single System Head

Used with any Nu-Plus[®] E Series filters. Head includes a water shut-off valve with mounting bracket and screws. (3/8" NPT)

4621-07

4621-01

QC7I Single Head

1 each

1 each

Ideal for all Nu-Plus[®] E Series filters. Head includes a shut off, flushing valve, and outlet pressure gauge on a box bracket design. (3/8[°] NPT)

QC7I Twin Parallel Head

Dual filter head that is parallel plumbed for two Nu-Plus[®] E Series filters, either mix or match. Head includes a shut off, flushing valve, and outlet pressure gauge on a box bracket design. (3/4" NPT)

1 each

4621-02

QC7I Triple Parallel Head

Triple filter head parallel plumbed for three Nu-Plus[®] E Series filters. Head includes a shut off, flushing valve, and outlet pressure gauge on a box bracket design. ($3/4^{"}$ NPT)

1 each 4621-03

QC7I Quad Parallel Head

Quad filter head parallel plumbed for four Nu-Plus[®] E Series filters. Head includes a shut off, flushing valve, and outlet pressure gauge on a box bracket design. (3/4" NPT)

1 each

4621-04

*Everpure® is a trademark of Everpure, Inc., Westmont, IL.



MRS-20 Reverse Osmosis System

Complete mineral reduction water processing system that removes at least 90%+ of all dissolved solids that cause scale build-up. The MRS-20 system removes taste and odor causing contaminants as well as dirt and particles. The two-part design makes installation flexible. It has no moving parts and requires no electrical power. System includes mineral reduction processor, carbon filter cartridge, reverse osmosis cartridge, and storage tank. No monitoring of grains per gallon is necessary.

MRS-20

9797-91



Kleensteam CT and Kleensteam II

Everpure's second generation water treatment system for steam applications.

Kleensteam is a total system delivering high quality filtered water with scale inhibition as well as deliming capabilities. The dual cartridge design provides enhanced performance for low and high flow capacity steamers and flexibility for expanding to meet future needs. Kleensteam also reduces chlorine-induced corrosion. It's simple to install, operate, and maintain.

| Kleensteam CT | 1.67 gpm max. flow | 9797-50 |
|---------------|--------------------|---------|
| Kleensteam II | 2.5 gpm max. flow | 9797-21 |



Nu-Plus E Series by Everpure High Flow CSR Manifold with Prefilter

Utilizing the nu-MC² or the nu-XC² cartridges, this system provides premium quality water to high flow fountain dispensers, coffee makers and ice machines. New and improved Micro-Pure II media inhibits the growth of bacteria. High Flow CSR reduces chlorine taste and odor and other offensive contaminants that can adversely effect the taste of beverages. Precoat submicron technology reduces dirt and particles as small as 1/2 micron and reduces health contaminants such as cysts. Additionally, the SRX Housing inhibits scale when it is equipped with scale-inhibiting IMF-10 ScaleSticks[®].

| High Flow CSR Manifold with Prefilter | | | |
|---------------------------------------|---------|---------|---------|
| | Twin | Triple | Quad |
| 10″ | 9294-02 | 9294-03 | 9294-04 |
| 20″ | 9294-22 | 9294-23 | 9294-24 |



Nu-Plus E Series by Everpure Coldrink/Insurice Systems

The Coldrink/Insurice manifolds can be used with any Nu-Plus by Everpure cartridges. i.e. the MC² or XC² for carbonated beverages or i2000² or i4000² for ice machines. Utilizes the systems' existing 10" or 20" pre-filter on a single, twin, triple, or quad manifold. Systems come with the initial EC110 or EC210 pre-filter cartidge. Just purchase the appropriate Nu-Plus by Everpure cartridge for your application.

| Coldrink/Insurice Manifold with Prefilter | | | | |
|---|---------|---------|---------|---------|
| | Single | Twin | Triple | Quad |
| 10″ | 9293-01 | 9293-02 | 9293-03 | 9293-04 |
| 20″ | 9293-21 | 9293-22 | 9293-23 | 9293-24 |

Cartridges









nu-i2000² and nu-i4000²

Reduces water-related ice machine problems caused by dirt, objectionable tastes and odor and scale build-up. Pre-coat submicron filtration reduces particles as small as 1/2 micron along with chlorine and other offensive contaminants. In addition, both cartridges use 6R Micromet^{*}, a highly acclaimed scale inhibitor that inhibits scale build-up caused by dissolved minerals. NSF registered under NSF/ANSI Standards 42 and 53.

- · Pre-coat filtration with Micro-Pure® II antibacterial protection
- Premier 6R Micromet scale control
- Cvst and asbestos fibers reduction
- Sanitary quick-change cartridge replacement

| nu-i2000² | 4621-10 | (NSF) |
|-------------------------------------|---|--------|
| apacity: 9 000 gallons • 750 lbs fo | or most cubers • 1,500 lbs. for most flaker | ~ |
| apacity: 27000 ganons 730 185.10 | | , , |

Capacity: 12,000 gallons • 1,000 lbs. for most cubers • 2,000 lbs. for most flakers

nu-MC² and nu-XC²

Reduces chlorine taste, odor and other offensive contaminants that can adversely affect the taste of fountain beverages. Pre-coat submicron filtration reduces particles as small as 1/2 micron, and it helps retain carbonation in drinks. NSF registered under NSF/ANSI Standards 42 and 53.

- · Pre-coat filtration with Micro-Pure® II antibacterial protection
- · Reduces objectionable tastes and odors
- · Cyst and asbestos fibers reduction
- Sanitary quick-change cartridge replacement

| 4621-20 | (NSE) |
|---------|-------|
| | |
| 4621-21 | (NSF) |
| | |

BH² and OCS² Cartridge

- Delivers premium quality water for ice and coffee applications
- Designed for applications where the i2000² is too long
- Precoat submicron particulate reduction
- Inhibits scale formation
- Taste and odor reduction
- NSF registered under NSF/ANSI standards 42 and 53.

| BH ² | 4621-12 | (NSF) |
|--|---------------------|-------|
| Capacity: 3,000 gallons or 6,000 pots of coffe | e•0.5 gpm max. flow | |
| OCS ² | 9618-07 | (NSF) |
| | 0.5 (1 | |

Capacity: 1,500 gallons or 3,000 pots of coffee • 0.5 gpm max. flow

OW200L and OW4Plus Cartridge

- Ideal for office or residential water systems
- Unique filter blend uses activated carbon to reduce chlorine taste, odor, and other offensive contaminants
- Reduces lead to below the Federal Action Level of 10 ppb
- Precoat submicron technology reduces dirt and particles as small as 1/2 micron
- Inhibits scale build-up in water-using appliances
- NSF registered under NSF/ANSI standards 42 and 53 •

| OW200L | 9619-06 | (NSE) |
|-----------------------|---------|-------|
| Capacity: 480 gallons | | |
| OW4 ^{PLUS} | 9635-06 | NCF |

Capacity: 2,000 gallons

*Everpure® is a trademark of Everpure, Inc., Westmont, IL.

Cartridges



4CB5, 7CB5, 4CB5-S, and nu-7CB5-S Cartridge

Carbon Block filter finely polishes water for high quality beverages and food applications. NSF registered under NSF Standard 42.

- Problem-solving cartridge for high particulate or low flow water pressure areas
- Taste and odor, chlorine reduction
- Particulate reduction to 5 micron
- 4CB5-S, and nu-7CB5-S cartridges control scale

| 4CB5 | 4621-32 | (NSF.) |
|--------------------------|---------------------------------------|------------|
| Capacity: 6,000 gallons | · · · · · · · · · · · · · · · · · · · | |
| 7CB5 | 9618-16 | (NSF) |
| Capacity: 10,000 gallons | | \sim |
| 4CB5-S | 4621-31 | (NSF) |
| Capacity: 6,000 gallons | | \bigcirc |
| nu-7CB5-S | 4621-30 | (NSF) |
| Capacity: 10,000 gallops | | \bigcirc |

Capacity: 10,000 gallons

4FC5, 7FC5, 4FC5-S, and 7FC5-S Cartridge

New Fiberdyne™ II media with Agion® antimicrobial protection to inhibit potential bacterial growth. Balanced for optimum performance in varying water qualities. Helps retain the drink's carbonation.

- Increased capacity 25,000 gallons
- Taste and odor reduction
- Particulate reduction
- 2.5 gpm flow rate .
- 5 micron rating •
- Scale inhibition (4FC5-S and 7FC5-S) .

| 7F05 | 7FG5-5 |
|------------------|-------------|
| 1. ÷. | |
| 4 4 4 25 | 4F05-5 |
| 2 | |
| and and a second | |
| 2 | M |
| States? | investori " |

| NSF standards 42 and 53 | | \frown |
|--------------------------|---------|------------|
| 4FC5 | 9693-21 | (NSF) |
| Capacity: 15,000 gallons | | \sim |
| 7FC5 | 9693-61 | (NSF) |
| Capacity: 25,000 gallons | | \bigcirc |
| 4FC5-S | 9693-31 | (NSF) |
| Capacity: 15,000 gallons | | |
| 7FC5-S | 9693-71 | (NSF) |
| Capacity: 25,000 gallons | | |



4FC, 7FC, 4FC-S, and 7FC-S Cartridge

New Fiberdyne[™] II media with Agion[®] antimicrobial protection to inhibit potential bacterial growth. Balanced for optimum performance in varying water qualities. Improves the taste of fountain drinks and helps retain the drink's carbonation.

| Taste and odor reductionParticulate reduction2.5 gpm flow rate | 0.5 micron rating NSF standards 42 and 53 Scale inhibition (4FC-S, and 7FC-S only) |
|--|--|
| 4FC | 9692-21 (NSF) |
| Capacity: 15,000 gallons | |
| 7FC | 9692-61 (NSF) |
| Capacity: 25,000 gallons | \sim |
| 4FC-S | 9692-31 (NSF) |
| Capacity: 15,000 gallons | |
| 7FC-S | 9692-71 (NSF) |
| Capacity: 25,000 gallons | |



Cartridges



4SI and 7SI Cartridge

Specially designed for ice machines. This cartridge does not include carbon, which allows for complicance with ASHRAE Standard 188. The cartridge reduces sediment and particulate down to 1/2 micron and reduces cyst and Giardia. The filter allows chlorine to pass through, which helps reduce slime and bacteria growth inside the ice machine and ice bin. Ideal for food service operations where baking of bread and pastries is done on-site.

Scale inhibition

- 0.5 micron rating
- Particulate reduction Cyst reduction
- NSF standards 42

NSF

| • Cyst reduction | | \frown |
|--|---------|---------------|
| 4SI | 9606-51 | (NSE) |
| Capacity: 15,000 gallons • 2.0 gpm flow rate | | |
| 7SI | 9606-01 | (NSE) |
| Capacity 25,000 gallons 2.5 gpm flow rate | | $\overline{}$ |

Capacity: 25,000 gallons • 3.5 gpm flow rate

7CLM Cartridge

Reduces chloramines, chlorine taste and odor and other offensive contaminants that can adversely affect the taste of beverages. The cartridge reduces particles down to 1/2 micron and reduces cysts and Giardia. Improves the taste of fountain beverages and helps retain the drink's carbonation. NSF registered.

| | Chloramine reduction Chlorine reduction | | Cyst reduction Particulate reduction | |
|---|---|----|---|--|
| | 7CLM | 96 | 93-01 | |
| (| Capacity: 3,600 gallons at 1.7 gpm, 5,500 gallons at 1.33 gpm | | | |

7SO Softening Cartridge

A softening cartridge that reduces scale-forming minerals like calcium and magnesium in hard water situations. It may be used on water having up to 30 grains hardness per gallon, at flow rates of up to 1/2 gallons per minute. It is a sanitary quick change cartridge that makes replacement easy. It should be used with an Everpure fine filter cartridge installed in a series plumbed twin head.

| 750 | 9607-04 | (NSF) |
|--|---------|-------|
| Capacity: 2,000 grains • 0.5 gpm max. flow | | |

Replacement Cartridges for CUNO[®]



Nu-Plus® CU and Nu-Plus CU-S

The Nu-Plus E Series CU and CU-S cartridges are replacements that are compatible with the CUNO Series CFS 8000 filter cartridges. Both incorporate a carbon block filter that reduces objectionable tastes and odors as well as chlorine and other contaminates, providing high guality beverage and ice. They also reduce extra fine dirt as small as 5 microns. Additionally, the CU-S provides for the reduction of scale formation.

| Nu-Plus CU | 4622-20 |
|--|---------|
| Capacity: 10,000 gallons (37,850 liters) • 1.5 gpr | n flow |
| Replaces CFS-8112, CFS-8720 & CFS-8812 | |
| • | |

Nu-Plus CU-S

Capacity: 10,000 gallons (37,850 liters) • 1.5 gpm flow Replaces CFS-8112S, CFS-8720S & CFS-8812S



4622-10

Other Filtration Products











Nu-Plus® 10" and 20" Coarse Prefilters

A 10[°] and 20[°] clear housing, each including a 10[°] and 20[°] replaceable prefilter cartridge. Filters out larger dirt and rust particles, thereby extending the life of submicron and carbon block filters.

| E-10 | 4621-42 |
|------|---------|
| E-20 | 4621-44 |

Optional: Wing Bracket for all multiple filter head systems manufactured after 2003: 4621-45

Nu-Plus® EC110 and EC210

A 10[°] and 20[°] 10-micron nominal filtration cartridge for filtering out larger dirt and rust particles, extending the life of primary filters. For use in the E-10 and E-20 housings as well as other 10[°] and 20[°] housings.

| EC110 (10 [″]) | 4621-41 |
|--------------------------|---------|
| EC210 (20 [″]) | 4621-43 |

SRX Scale Inhibitor Feeder

A complete system for the control of scale in ice, coffee, steam, and combination applications. It dispenses a controlled amount of HydroBlend[®] compound, which provides for a more consistent feed and longer life. The system includes a clear housing and one cartridge

| 1 each | 4621-05 | |
|--------|---------|--|
| | | |

Optional: Wing Bracket for all multiple filter head systems manufactured after 2003: 4621-06

Nu-Plus® IMF-7 and IMF-10

Ice Machine Feeder Scale inhibition cartridge. The translucent cartridge allows for easy visual monitoring of the product's usage. The larger IMF-10 will last longer or treat higher volumes of water.

| IMF-7 | Replacement for AR-X 7 ["] Housing | 4621-13 |
|--------|---|---------|
| IMF-10 | Replacement for SS-10 Scale Sticks | 4621-14 |

4JT Flushing/Sanitizing Cartridge

The preferred way to introduce ScaleKleen[™] Scale Remover or other sanitizing solutions (IMS-III) into all water-using equipment and vending machines. Fits into existing Everpure heads. Eliminates the need for difficult component disassembly. Easy and convenient to help you clean and maintain equipment. Approved by NAMA.

| 1 each | 4621-00 |
|--------|---------|
| | |



ScaleKleen[™] Scale Remover

Restores equipment to peak operating efficiency by removing scale build-up. Quickly removes limescale from coffee brewers. Ideal for deliming steam and ware washing equipment. Great for office coffee system (OCS) applications. Non-toxic, safe to skin and won't burn clothing. Sewer system disposable; can be poured down the drain. Use with 4JT Flushing/Sanitizing Cartridge.

| 7 ounce packets (24 per case) | 4621-17 |
|-------------------------------|---------|
| 2.2 lb. canister (4 per case) | 9798-35 |

40

NATE training now online. Visit us at www.nucalgon.com.

Coil Cleaning: The Clean Coil Program is a comprehensive seminar dedicated to the safe and proper procedures to clean evaporator and condenser coils. The program will help determine which cleaning method should be utilized for a particular job based on the type and condition of the unit. NATE Recognition Classes: 1 hour Continuing **Education Accreditation** NATE In

Ice Machine Treatment and Filtration: A complete guide to "Extending the Life of an Ice Machine." The seminar will answer the questions: why use a filter, what filter should be used, and how to keep the system clean, clear, and running properly. It also addresses all of the water-related problems associated with ice machines. (1.5 hours)

Indoor Air Quality Management: The seminar covers the past, present and future of indoor air quality (IAQ). Topics covered in the session: how poor IAQ impacts a business, common causes of poor IAQ, and how to prevent poor IAQ from occurring. NATE Recognition Classes: 1 hour Continuing Education Accreditation

Nu-Calgon Product Line Review: The seminar provides an overview of all the major products that Nu-Calgon offers. The presentation explores when and where to use certain products, as well as explains how using certain products can save time and money. (2 hours)

Refrigeration Oils: An in-depth look at industry refrigeration oils (Mineral, Alkylbenzene, and POE) and when and where to use them. NATE Recognition Classes: 1.5 hours Continuing Education Accreditation NATÉ LONG

Total System Protection: A thorough look at why burnouts occur, how to prevent them and the proper way to flush a system once a burnout occurs. The training will include acid testing and acid neutralization. NATE Recognition Classes: 1 hour Continuing Education Accreditation

Water Treatment: This seminar will cover the fundamentals of water treatment for cooling towers, evaporative condensers, boilers, and chillers. NATE Recognition Classes: 1.5 hours Continuing Education Accreditation

Winter Water Treatment: This program focuses on what a system needs prior to the winter season, including a review of ethylene and propylene glycol, the proper treatments for hot/cold closed systems, and low make-up steam systems. (1 hour)

Energy Savings with A/C Re-New: Learn about a revolutionary product for revitalizing and energizing A/C systems. The seminar will explain how A/C Re-New will help reduce energy costs, improve cooling performance and reduce the system noise. (1 hour)

Food Service Products for Ice & Beverage Filtration: A comprehensive look at the problems associated with ice and beverage filtration as well as treatment options to solve these problems. We will cover products for ice makers, coffee brewers, fountain beverage machines, steam ovens, drinking water, and more. (1 hour)











- 1. Seattle, WA
- 2. Northern CA
- 3. Southern CA
- 4. Los Angeles, CA
- 5. San Diego, CA
- 6. Phoenix, AZ
- 7. Denver, CO
- 8. San Antonio, TX
- 9. Dallas Fort Worth
- 10. Houston, TX

- 11. Kansas City, MO
- 12. St. Paul Minneapolis
- 13. St. Louis, MO
- 14. Baton Rouge, LA
- 15. Milwaukee, WI
- 16. Chicago, IL
- 17. Indianapolis, IN
- 18. Columbus, OH
- 19. Birmingham, AL
- 20. Atlanta, GA

- 21. Ocala, FL
- 22. Tampa, FL
- 23. Miami, FL
- 24. Raleigh, NC
- 25. Richmond, VA
- 26. Baltimore, MD
- 27. Philadelphia, PA
- 28. NYC/New Jersey
- 29. Syracuse, NY
- 30. Boston, MA
- 🛠 St. Louis, MO (Hdq.)

















Nu-Calgon 2008 Altom Court | St. Louis, M0 63146 phone: 800-554-5499 | fax: 800-221-6302 www.nucalgon.com

(416) 3-300 | Calgon is a licensed trade name.