



**Materials:**

- Screws conform to SAE J429 GR 2 (exceeds ASTM A307).

**Finishes:**

- **Electrogalvanized (EG):**  
Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):**  
Conforms to ASTM A1059

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 316 (SS):** ASTM A240, Type 316 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	Thread Size	Length (ft)	Finish	Product Weight / Piece (lbs)
PS 602 4 1/2" x 1-1/2"	1/2"	1-1/2"	EG	0.116
PS 602 4 1/2" x 1-1/2"	1/2"	1-1/2"	DF	0.116
PS 602 4 1/2" x 1-1/4"	1/2"	1-1/4"	EG	0.11
PS 602 4 1/2" x 1-3/16"	1/2"	1-3/16"	EG	0.102
PS 602 4 1/2" x 1-3/16"	1/2"	1-3/16"	DF	0.102
PS 602 4 1/2" x 1-3/4"	1/2"	1-3/4"	EG	0.131
PS 602 4 1/2" x 15/16"	1/2"	15/16"	EG	0.091
PS 602 4 1/2" x 15/16"	1/2"	15/16"	DF	0.091
PS 602 4 1/2" x 2"	1/2"	2"	EG	0.146
PS 602 4 1/2" x 2-1/2"	1/2"	2-1/2"	EG	0.175
PS 602 4 1/2" x 2-1/4"	1/2"	2-1/4"	EG	0.16
PS 602 4 1/4" x 1"	1/4"	1"	EG	0.02
PS 602 4 1/4" x 1-1/2"	1/4"	1-1/2"	EG	0.026
PS 602 4 1/4" x 1-1/2"	1/4"	1-1/2"	DF	0.026
PS 602 4 1/4" x 3/4"	1/4"	3/4"	EG	0.013
PS 602 4 1/4" x 3/4"	1/4"	3/4"	DF	0.013
PS 602 4 1/4" x 7/16"	1/4"	7/16"	EG	0.01
PS 602 4 3/8" x 1"	3/8"	1"	EG	0.045
PS 602 4 3/8" x 1"	3/8"	1"	DF	0.045

PS 602 4 3/8" x 1-1/2"	3/8"	1-1/2"	EG	0.06
PS 602 4 3/8" x 1-1/2"	3/8"	1-1/2"	DF	0.06
PS 602 4 3/8" x 1-1/4"	3/8"	1-1/4"	EG	0.053
PS 602 4 3/8" x 2"	3/8"	2"	EG	0.076
PS 602 4 3/8" x 2-1/2"	3/8"	2-1/2"	EG	0.092
PS 602 4 3/8" x 2-1/4"	3/8"	2-1/4"	EG	0.084
PS 602 4 3/8" x 3/4"	3/8"	3/4"	EG	0.04
PS 602 4 3/8" x 7/8"	3/8"	7/8"	EG	0.044
PS 602 4 5/16" x 1-1/4"	5/16"	1-1/4"	EG	0.036

<b>Project:</b>	<input type="text"/>		
<b>Architect / Engineer:</b>	<input type="text"/>		
<b>Date:</b>	<input type="text"/>	<b>Phone:</b>	<input type="text"/>
<b>Contractor:</b>	<input type="text"/>		
<b>Address:</b>	<input type="text"/>		
<b>Notes:</b>	<input type="text"/>		

**Approval Stamp:**