



#### Materials & Finishes - Standard:

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1
- **Plain (PL):** No finish

#### Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 \*
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 \*
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

| Part No.       | A       | B             | Finish | Product Weight / Piece (lbs) |
|----------------|---------|---------------|--------|------------------------------|
| PS 781 15°     | 15°     | 3-3/4" (95)   | EG     | 0.78                         |
| PS 781 15°     | 15°     | 3-3/4" (95)   | HG     | 0.78                         |
| PS 781 15°     | 15°     | 3-3/4" (95)   | GR     | 0.78                         |
| PS 781 22-1/2° | 22-1/2° | 3-3/4" (95)   | EG     | 0.78                         |
| PS 781 22-1/2° | 22-1/2° | 3-3/4" (95)   | HG     | 0.78                         |
| PS 781 22-1/2° | 22-1/2° | 3-3/4" (95)   | GR     | 0.78                         |
| PS 781 30°     | 30°     | 3-11/16" (94) | EG     | 0.78                         |
| PS 781 30°     | 30°     | 3-11/16" (94) | HG     | 0.78                         |
| PS 781 30°     | 30°     | 3-11/16" (94) | GR     | 0.78                         |
| PS 781 37-1/2° | 37-1/2° | 3-11/16" (94) | EG     | 0.78                         |
| PS 781 37-1/2° | 37-1/2° | 3-11/16" (94) | HG     | 0.78                         |
| PS 781 37-1/2° | 37-1/2° | 3-11/16" (94) | GR     | 0.78                         |
| PS 781 45°     | 45°     | 3-11/16" (94) | EG     | 0.78                         |
| PS 781 45°     | 45°     | 3-11/16" (94) | DF     | 0.78                         |
| PS 781 45°     | 45°     | 3-11/16" (94) | HG     | 0.78                         |
| PS 781 45°     | 45°     | 3-11/16" (94) | GR     | 0.78                         |
| PS 781 52-1/2° | 52-1/2° | 3-11/16" (94) | EG     | 0.78                         |
| PS 781 52-1/2° | 52-1/2° | 3-11/16" (94) | HG     | 0.78                         |
| PS 781 52-1/2° | 52-1/2° | 3-11/16" (94) | GR     | 0.78                         |
| PS 781 60°     | 60°     | 3-11/16" (94) | EG     | 0.78                         |
| PS 781 60°     | 60°     | 3-11/16" (94) | HG     | 0.78                         |
| PS 781 60°     | 60°     | 3-11/16" (94) | GR     | 0.78                         |
| PS 781 67-1/2° | 67-1/2° | 3-5/8" (91)   | EG     | 0.78                         |
| PS 781 67-1/2° | 67-1/2° | 3-5/8" (91)   | HG     | 0.78                         |
| PS 781 67-1/2° | 67-1/2° | 3-5/8" (91)   | GR     | 0.78                         |
| PS 781 7-1/2°  | 7-1/2°  | 3-3/4" (95)   | EG     | 0.78                         |
| PS 781 7-1/2°  | 7-1/2°  | 3-3/4" (95)   | HG     | 0.78                         |
| PS 781 7-1/2°  | 7-1/2°  | 3-3/4" (95)   | GR     | 0.78                         |
| PS 781 75°     | 75°     | 3-5/8" (91)   | EG     | 0.78                         |
| PS 781 75°     | 75°     | 3-5/8" (91)   | HG     | 0.78                         |
| PS 781 75°     | 75°     | 3-5/8" (91)   | GR     | 0.78                         |
| PS 781 82-1/2° | 82-1/2° | 3-5/8" (91)   | EG     | 0.78                         |
| PS 781 82-1/2° | 82-1/2° | 3-5/8" (91)   | HG     | 0.78                         |
| PS 781 82-1/2° | 82-1/2° | 3-5/8" (91)   | GR     | 0.78                         |

Project:

Architect / Engineer:

Date:

Phone:

Contractor:

Address:

Notes:

Approval Stamp: