

WW-RSL SERIES LINERED RUBBER SPLICING TAPE - 600V

DESCRIPTION				FEATURES	
 WW-RSL is a 30 mil (0.76mm) self-amalgamating, low voltage rubber tape which is UL-510 Listed for use as primary insulation at not more than 600 volts. It easily conforms to irregular shapes and surfaces yielding a void free electrically stable build-up. WW-RSL is compatible with all extruded dielectric cable insulations. Meet ASTM D-4388 type I standard. Self- amalgamating Good electrical properties Good conformability Rated up to 600V Linered 					erties
MATERIALS	BACKING	ADHESIVE	COLOR	STANDARD SIZES (WIDTH X LENGTH)	PART NUMBER
	Rubber	None	Black	.75" x 22' (19mm x 6.7m) 1" x 22' (25mm x 6.7m) 1.5" x 22' (38mm x 6.7m) 2" x 22' (51mm x 6.7m)	WW-RSL-75 WW-RSL-10 WW-RSL-15 WW-RSL-20
TECHNICAL PROPERTIES	CHARACTERISTIC	TYPICAL VALUE		TEST METHOD	
	Thickness (mils)	30		UL 510	
	Tensile strength (psi)	435.11		UL 510	
	Elongation (%)	500		UL 510	
	Flammability	Pass		UL 510	
	Operating temp.: Continuous	176°F, 80°C		UL 510	
	Weather resistance	Pass		UL 510	
	Dielectric strength (V/mil)	508		UL 510	
RECOMMENDED USES		STORAGE		SHELF LIFE	
For insulating of splices on solid dielectric cable through 600 volts in conjunction with a jacketing tape		In original packaging, placed in horizontal position under cover and temperature between 5°C and 35°C.		24 months from date of manufacture.	

Data in table represents average test results and are not to be used for specification purpose. The product users should make their own tests to determine the products' suitability for the intended use

LIMITED WARRANTY: NSi Industries LLC warrants that each of its products will be free from material and manufacture defects at the date of shipment (unless specified otherwise). NSi Industries LLC makes or gives no warranty to the distributor, its customers, or the product's end user regarding the product's merchantability and/or suitability for their/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proven to be defective, NSi Industries sole obligation and buyer's exclusive remedy shall be through the distributor, at NSi Industries' discretion, to replair, or refund the product proved to be defective within the time period specified above. EXCEPT AS EXPRESSLY SET FORTH HEREIN, NSI INDUSTRIES MAKES OR GIVES NO OTHER WARRANTIES, EXPRESSED OR IMPLIED. Except where prohibited by law, NSi Industries LLC will not be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products.