

# Product data sheet

Specifications

SQUARE D



## Thermal Unit, Type S, Type B, melting alloy, Class 20

B12.8

Product availability: Stock - Normally stocked in distribution facility

### Main

Range of Product	B
Thermal overload type	Melting alloy
Motor tripping class	20

### Ordering and shipping details

Category	US10CP121781
Discount Schedule	0CP1
GTIN	785901587491
Returnability	Yes
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	1.10 in (2.8 cm)
Package 1 Length	2.28 in (5.8 cm)
Package weight(Lbs)	0.8 oz (22.7 g)

### Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.


## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.


[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
PVC free	Yes


### Use Again

 <b>Repack and remanufacture</b>	
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration

Dimensions

---



ALL DIMENSIONS ARE APPROXIMATE.  
ALSO SEE CAD, TECHNICAL DRAWINGS, AND DOCUMENTATION.