



Materials:

- Screws conform to SAE J429 GR 2 (exceeds ASTM A307).

Finishes:

- **Electrogalvanized (EG):**
Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):**
Conforms to ASTM A1059

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 316 (SS):** ASTM A240, Type 316 *

* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	Thread Size	Length (ft)	Finish	Product Weight / Piece (lbs)
PS 607 5 14" x 1"	1/4"	1"	EG	0.019
PS 607 5 14" x 1/2"	1/4"	1/2"	EG	0.014
PS 607 5 14" x 1-1/2"	1/4"	1-1/2"	EG	0.04
PS 607 5 14" x 1-1/4"	1/4"	1-1/4"	EG	0.03
PS 607 5 14" x 3/4"	1/4"	3/4"	EG	0.017
PS 607 5 14" x 5/8"	1/4"	5/8"	EG	0.015
PS 607 5 3/8" x 1-1/4"	3/8"	1-1/4"	EG	0.053
PS 607 5 5/16" x 1"	5/16"	1"	EG	0.026
PS 607 5 5/16" x 1-1/2"	5/16"	1-1/2"	EG	0.034
PS 607 5 5/16" x 1-1/4"	5/16"	1-1/4"	EG	0.03
PS 607 5 5/16" x 1-3/4"	5/16"	1-3/4"	EG	0.04

Project:

Architect / Engineer:

Date: **Phone:**

Contractor:

Address:

Notes:

Approval Stamp: