



#### Materials & Finishes - Standard:

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1
- **Plain (PL):** No finish

#### Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 \*
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 \*
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

| Part No.       | A       | B              | C            | Finish | Product Weight / Piece (lbs) |
|----------------|---------|----------------|--------------|--------|------------------------------|
| PS 633 15°     | 15°     | 3-5/16" (84.1) | 2-1/16"      | EG     | 0.58                         |
| PS 633 22-1/2° | 22-1/2° | 3-5/16" (84.1) | 2-1/16"      | EG     | 0.58                         |
| PS 633 30°     | 30°     | 3-1/4" (82.6)  | 2-1/16"      | EG     | 0.58                         |
| PS 633 30°     | 30°     | 3-1/4" (82.6)  | 2-1/16"      | HG     | 0.615                        |
| PS 633 30°     | 30°     | 3-1/4" (82.6)  | 2-1/16"      | GR     | 0.58                         |
| PS 633 30°     | 30°     | 3-1/4" (82.6)  | 2-1/16"      | SS     | 0.58                         |
| PS 633 37-1/2° | 37-1/2° | 2-11/16"       | 2-5/8"       | EG     | 0.58                         |
| PS 633 45°     | 45°     | 3" (76)        | 2-5/16" (59) | EG     | 0.58                         |
| PS 633 45°     | 45°     | 3" (76)        | 2-5/16" (59) | DF     | 0.615                        |
| PS 633 45°     | 45°     | 3" (76)        | 2-5/16" (59) | HG     | 0.615                        |
| PS 633 45°     | 45°     | 3" (76)        | 2-5/16" (59) | GR     | 0.58                         |
| PS 633 45°     | 45°     | 3" (76)        | 2-5/16" (59) | SS     | 0.58                         |
| PS 633 45°     | 45°     | 3" (76)        | 2-5/16" (59) | AL     | 0.23                         |
| PS 633 52-1/2° | 52-1/2° | 3-1/4"         | 2-1/16"      | EG     | 0.58                         |
| PS 633 60°     | 60°     | 3-3/8"         | 1-7/8"       | EG     | 0.58                         |
| PS 633 60°     | 60°     | 3-3/8"         | 1-7/8"       | HG     | 0.615                        |
| PS 633 60°     | 60°     | 3-3/8"         | 1-7/8"       | GR     | 0.58                         |
| PS 633 60°     | 60°     | 3-3/8"         | 1-7/8"       | SS     | 0.58                         |
| PS 633 67-1/2° | 67-1/2° | 3-1/2"         | 1-3/4"       | EG     | 0.58                         |
| PS 633 7-1/2°  | 7-1/2°  | 3-5/16" (84.1) | 2-1/16"      | EG     | 0.55                         |
| PS 633 75°     | 75°     | 3-9/16"        | 1-11/16"     | EG     | 0.58                         |
| PS 633 82-1/2° | 82-1/2° | 3-9/16"        | 1-11/16"     | EG     | 0.58                         |

Project:

Architect / Engineer:

Date:

Phone:

Contractor:

Address:

Notes:

Approval Stamp: