

**Materials & Finishes - Standard:**

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1
- **Plain (PL):** No finish

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 \*
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 \*
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	A	B	Finish	Product Weight / Piece (lbs)
P1788 3/4"	1.86 (47)	2.34 (59)	SS	0.37
P1788 3/4"	1.86 (47)	2.34 (59)	EV	0.37
P1789 1-1/4"	2.36 (60)	2.86 (73)	SS	0.58
P1789 1-1/4"	2.36 (60)	2.86 (73)	EV	0.58
P1790 1-3/4"	2.86 (73)	3.50 (89)	SS	0.76
P1790 1-3/4"	2.86 (73)	3.50 (89)	EV	0.76
P1791 2-1/4"	3.36 (85)	4.05 (103)	SS	0.9
P1791 2-1/4"	3.36 (85)	4.05 (103)	EV	0.9
P1792 2-3/4"	3.86 (98)	4.75 (121)	SS	1.09
P1792 2-3/4"	3.86 (98)	4.75 (121)	EV	1.09
P1794 3-3/4"	4.86 (184)	5.54 (141)	SS	1.6
P1794 3-3/4"	4.86 (184)	5.54 (141)	EV	1.6
P1795 4-1/4"	5.24 (133)	5.92 (150)	SS	1.6
P1795 4-1/4"	5.24 (133)	5.92 (150)	EV	1.6
PS 722 1"	1.86 (47)	2.34 (59)	SS	0.37
PS 722 1"	1.86 (47)	2.34 (59)	EV	0.37
PS 722 1/2"	1.36 (35)	1.82 (46)	SS	0.25
PS 722 1/2"	1.36 (35)	1.82 (46)	EV	0.25
PS 722 1-1/2"	2.36 (60)	2.86 (73)	SS	0.58
PS 722 1-1/2"	2.36 (60)	2.86 (73)	EV	0.58
PS 722 1-1/8"	1.86 (47)	2.34 (59)	SS	0.37
PS 722 1-1/8"	1.86 (47)	2.34 (59)	EV	0.37
PS 722 1-3/8"	2.36 (60)	2.86 (73)	SS	0.58
PS 722 1-3/8"	2.36 (60)	2.86 (73)	EV	0.58
PS 722 1-5/8"	2.36 (60)	2.86 (73)	SS	0.58
PS 722 1-5/8"	2.36 (60)	2.86 (73)	EV	0.58
PS 722 1-7/8"	2.86 (73)	3.50 (89)	SS	0.76
PS 722 1-7/8"	2.86 (73)	3.50 (89)	EV	0.76
PS 722 2"	2.86 (73)	3.50 (89)	SS	0.76
PS 722 2"	2.86 (73)	3.50 (89)	EV	0.76
PS 722 2-1/2"	3.36 (85)	4.05 (103)	SS	0.9
PS 722 2-1/2"	3.36 (85)	4.05 (103)	EV	0.9
PS 722 2-1/8"	2.86 (73)	3.50 (89)	SS	0.76
PS 722 2-1/8"	2.86 (73)	3.50 (89)	EV	0.76
PS 722 2-3/8"	3.36 (85)	4.05 (103)	SS	0.9
PS 722 2-3/8"	3.36 (85)	4.05 (103)	EV	0.9
PS 722 2-5/8"	3.36 (85)	4.05 (103)	SS	0.9
PS 722 2-5/8"	3.36 (85)	4.05 (103)	EV	0.9
PS 722 2-7/8"	3.86 (98)	4.75 (121)	SS	1.09
PS 722 2-7/8"	3.86 (98)	4.75 (121)	EV	1.09
PS 722 3"	3.86 (98)	4.75 (121)	SS	1.09
PS 722 3"	3.86 (98)	4.75 (121)	EV	1.09
PS 722 3/8"	1.36 (35)	1.82 (46)	SS	0.25
PS 722 3/8"	1.36 (35)	1.82 (46)	EV	0.25
PS 722 3-1/2"	4.36 (111)	5.125 (130)	SS	1.3
PS 722 3-1/2"	4.36 (111)	5.125 (130)	EV	1.3
PS 722 3-1/4"	4.36 (111)	5.125 (130)	SS	1.3
PS 722 3-1/4"	4.36 (111)	5.125 (130)	EV	1.3
PS 722 3-1/8"	3.86 (98)	4.75 (121)	SS	1.09
PS 722 3-1/8"	3.86 (98)	4.75 (121)	EV	1.09

PS 722 3-3/8"	4.36 (111)	5.125 (130)	SS	1.3
PS 722 3-3/8"	4.36 (111)	5.125 (130)	EV	1.3
PS 722 3-5/8"	4.36 (111)	5.125 (130)	SS	1.3
PS 722 3-5/8"	4.36 (111)	5.125 (130)	EV	1.3
PS 722 3-7/8"	4.86 (184)	5.54 (141)	SS	1.6
PS 722 3-7/8"	4.86 (184)	5.54 (141)	EV	1.6
PS 722 4"	4.86 (184)	5.54 (141)	SS	1.6
PS 722 4"	4.86 (184)	5.54 (141)	EV	1.6
PS 722 4-1/2"	5.24 (133)	5.92 (150)	SS	1.6
PS 722 4-1/2"	5.24 (133)	5.92 (150)	EV	1.6
PS 722 4-1/8"	4.86 (184)	5.54 (141)	SS	1.6
PS 722 4-1/8"	4.86 (184)	5.54 (141)	EV	1.6
PS 722 4-3/8"	5.24 (133)	5.92 (150)	SS	1.6
PS 722 4-3/8"	5.24 (133)	5.92 (150)	EV	1.6
PS 722 5/8"	1.36 (35)	1.82 (46)	SS	0.25
PS 722 5/8"	1.36 (35)	1.82 (46)	EV	0.25
PS 722 7/8"	1.86 (47)	2.34 (59)	SS	0.37
PS 722 7/8"	1.86 (47)	2.34 (59)	EV	0.37

<b>Project:</b>	<input type="text"/>		
<b>Architect / Engineer:</b>	<input type="text"/>		
<b>Date:</b>	<input type="text"/>	<b>Phone:</b>	<input type="text"/>
<b>Contractor:</b>	<input type="text"/>		
<b>Address:</b>	<input type="text"/>		
<b>Notes:</b>	<input type="text"/>		

**Approval Stamp:**