



**Materials & Finishes - Standard:**

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1
- **Plain (PL):** No finish

Part No.	A	Finish	Flange Thickness	Product Weight / Piece (lbs)
PS 998	3/8" (10)	EG	Up to 3/4" (Up to 19)	0.62
PS 998	3/8" (10)	HG	Up to 3/4" (Up to 19)	0.657
PS 998	3/8" (10)	GR	Up to 3/4" (Up to 19)	0.62

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 \*
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 \*
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

<b>Project:</b>	<input type="text"/>		
<b>Architect / Engineer:</b>	<input type="text"/>		
<b>Date:</b>	<input type="text"/>	<b>Phone:</b>	<input type="text"/>
<b>Contractor:</b>	<input type="text"/>		
<b>Address:</b>	<input type="text"/>		
<b>Notes:</b>	<input type="text"/>		

**Approval Stamp:**