

HMT V35 Pipe Magnet Drill

The V35 Pipe Magnet Drill offers all the advantages of the standard V35 with the added benefit of a pipe compatible magnetic base.

Two switched permanent magnets are secured to swivelling mounting points and can be positioned as needed, allowing use on tubes and piping with a minimum diameter of 3". This also allows use on many contoured surfaces and internal use on large pipes.

Magnets can also be positioned horizontally to use as a standard machine on flat surfaces.



FEATURES & BENEFITS

- Use on both contoured and flat surfaces
- Two switched permanent magnets with individual swivel action
- Use on pipe/tubing internally and externally as needed (min diameter 3")
- Supplied with coolant fed arbor

TECHNICAL SPECIFICATIONS

CUTTER SIZE RANGE	1/2" - 1-3/8" TCT
MAX CUTTER CAPACITY	1-3/8" TCT
DEPTH OF CUT	4"
TWIST DRILL CAPACITY	1/2"
COUNTERSINKING	1"
REAMING	N/A
MAX TAP CAPACITY	N/A
STROKE	5-1/2"
LENGTH	11"
WIDTH (Inc Handles)	7-1/2"
HEIGHT (Min-Max)	13" - 18-1/2"
WEIGHT	23.15 lb
MAGNET (L X W X H)	7.5" x 6-1/2" x 3-1/4"
MAGNETIC ADHESION	1173 lb
MOTOR POWER	850W
TOTAL POWER	900W
SPEED RPM (No Load)	750
SPINDLE	3/4" Weldon
ARBOR	Integral 3/4" Weldon
COOLANT SYSTEM	Gravity Oil Fed
WARRANTY	2 Year (When registered)



Part No	Contents
850035-T-110US	V35 PIPE Magnet Drill Kit 110V

Supplied with **STAKIT** case, VersaDrive® Rapid-Lock adapter, handles, restraint strap, heavy duty metal guard & gravity fed coolant system.

