WIFI Optional Fully functional without internet access. New construction, no password, no problem.

Universal Subbase No wiring necessary. Fast, easy upgrade

Technician Private Label

Contractor contact info displayed in mobile

WIFI Made Simple

Our customized, innovative, efficient products are chosen

by thousands of heating and cooling professionals. We

bring the same level of performance and simplicity to the connected thermostat market with our new line of WIFI thermostats. The T701i is perfect for the everyday homeowner who wants to keep it simple. The T855i is great for all of those advanced jobs that require advanced

features, multiple stages or commercial settings.

 (\mathbf{U})

app and on the magnetic badge **Active Alerts**

Receive alerts from anywhere.

High and low temp. limits, connection status, and more.

Control Remotely Scheduling

Private Label

www.pro1iag.com 1-800-Pro1-559



Multiple Locations

estions about your



v. 1507

T800 Family

Held/Due



Ĩ**[**]:[]3ľ

T900 Family



Removable Badge System

(¹) High Quality

Pro1 thermostats are contractor grade, built on the proven performance and reliability you expect. It's a difference you can feel.

(1)**One Size Thermostats**

All Pro1 thermostats have the same size footprint, so you never have to worry about wall marks left by old models. You can also upgrade to new models including Wi-Fi without rewiring using the interchangeable subbase system.

(¹) Full Offering

We offer a full line of thermostats for nearly every application. Whether you need a basic 1 heat, 1 cool non-programmable or a 4 heat, 2 cool Wi-Fi thermostat, Pro1 has you covered.

(¹) Badge System

All Pro1 thermostats share a removable badge that can easily be replaced with a custom badge that has your contact information. This free service is a great way to generate future business for your company.











Exclusively for Contractors

Heavy duty products for HVAC Professionals



Are you a **PRU**?











Model # Nomenclature
Prefix
 T Thermostats - DA Discharge air sensor R Remote sensor - Z Zoning capable
First Number
6 600 platform - 8 800 platform7 700 platform - 9 900 platform
Second Number
 0 Single stage - 3 Universal PTAC 1 Multi stage gas - 5 Universal multi stage 2 Multi stage heat pump - 7 Heating or cooling
Third Number
1 Non-Programmable 5 Programmable
Suffix
 W Wireless - S Wired Remote Sensor Capable H Humidity Control2 Series Number i Internet Capable

	F	 Commercial 2/4 Time Perior (Occupied/Unoccupied) 7 Day Programmable 5/1/1 Programmable 		/							Dual Competentie	Displ.	Auto Sie Squar	Ver hches	Room I Change Remi	ature	Con Time Conditions	Adjustant Short	are of	Suin 00/	Procent Space	of Fan Switch	140 Equipancy Fan in	Almerson Color Mage	olay Lich	Humide Ser	Doint Line	Sun. 101	Remote Remained	Te Sensor Goable	Heeron.			
	Pro1	NP Non-Programmable	/	St. Of Ha.		the floctric of	Min Pump	 *	Zali Power	Outoo Outor Hair			2,5 A	Filton Deover	7. 196	Allbation entre			eratura	Hing Fan Do		Pre-O nable L			40: 001 001	1906 Se	Menie Cont			(e ^{.26})				
	Model #	5/2 Programming From App	/ క	š/5	<u>ي (م</u>	5) ×	ies/	Base	241, Zali,				Auto	Filton		Minin Dinin		A Click					50K	Thung the			Ken .		, Femo 1	/	Terminals			
	WIFI			1	1		1	1											1						1									
T855i		7D 5/1/1 NP 5/2 C	4*	2	•	•			•		•	8	•	•	•	•	•	•	•		•	•	• •	•	•	_	•	┥			C, Y, Y2, W/E, W2, G, O, B			
	T701i Wireless	NP **	1	1	•	•			•			4			•		•	•					•				•			Rh, Rc, C,	Y, W, G, O, B			
	Z955W	7D 5/1/1 NP	3*	2	•	•		•	•	•	•	13		•	•	•	•	•	•		•			•	•		•	•		Rh, Rc, C,	C, Y, Y2, W/E, W2, G, O, B			
	T955WH	7D 5/1/1 NP C	3*		•	•		•	•	•	•	13	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•			ſ, Y2, W/E, W2, G, O, B, H, D			
T631W-2		NP	2	1	•	•		•	•			2			•		•	•		•		Т			•		•	Т		R, C, Y, W,	GH, GL, 0/B			
	Wired		•	0								1.0																						
SТ	T955	7D 5/1/1 NP C 7D 5/1/1 NP	3*	2	•	•	•	•	•		•	13	•	•	•	•	•	•	•		•	•		•	•	_		•			Y, Y2, W/E, W2, G, O, B			
BE	T925 T905	7D 5/1/1 NP 7D 5/1/1 NP	3	2	•	•	•	•	•		•	13 13	•	•	•	•	•	•			•	-		•	•	_	-	•		R, C, Y, Y2, W2, E, G, O, B, L Rh, Rc, C, Y, W, G, O, B				
	1905								•				•	-	-		•				•						-							
ER	T855	7D 5/1/1 NP C	3*	2	•	•	•	•	•		•	8	•	•	•	•	•	•	•		•	•	• •		•	_	•	\rightarrow		Rh, Rc, C, Y, Y2, W/E, W2, G, O, B				
BETT	T805	7D 5/1/1 NP			•	•	•	•	•			8	•	•	•	•	•	•			•			•	•	_	•	4	-	Rh, Rc, C, Y, W, G, O, B				
	T801	NP			•	•	•	•	•			8	•	•	•	•	•	•						•	•		•			Rh, Rc, C,	Y, W, G, O, B			
	T771	NP	0/1	0/1	•		•	•	•			4			•		•	•							•		•			R, C, W/Y, G				
	T755H	5/1/1 NP	3*	2	•	•	•	•	•		•	6		•	•	•	•	•	•		•				•	•	•	\downarrow		Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, H, D				
	T755S	5/1/1 NP	3*	2	•		•	•	•	•	•	6		•	•	•	•	•	•		•				•		•	4		Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, S1, S2				
OD	T755	5/1/1 NP	3*	2	•	•	•	•	•		•	6		•	•	•	•	•	•		•		_		•	_	•	╉		Rh, Rc, C, Y, Y2, W/E, W2, G, O, B				
GC	T725	5/1/1	2	1		-		•	•		•	4		•	•	•	•	•										+	-	R, C, Y, W2, E, G, O, B R, C, Y, W2, E, G, O, B				
	T721	NP	2	1	•			•	•		•	4		•	•	•	•	•				_					•	╈						
	T715 T705	5/1/1	2	2	•	•	•	•	•			4		•	•	•	•	•				-					•	+	-	Rh, Rc, C, Y, Y2, W, W2, G, O, B				
	T703	5/1/1 NP	1	1	•		•	•	•			4		•	•	•	•	•				+	-				•	╈		Rh, Rc, C, Y, W, G, O, B Rh, Rc, C, Y, W, G, O, B				
	T631-2	NP	2	1	•	•		•	•			2			•		•	•		•					•		•	+	_	R, C, Y, W, GH, GL, O/B				
DER	T621-2	NP	2			•		•	•		•	2			•		•	•				_	_				•	┢	_	R, C, Y, W2, E, G, O, B				
BUIL	T605-2	5/1/1 NP	1		•	•	•	•	•			2		•	•	•	•	•				_	_				•	+		Rh, Rc, C, Y, W, G, O, B Rh, Rc, C, Y, W, G, O, B				
	T601-2	NP	I		•	•	•	•	•			2 сом	PATIBLI	WITH	•		•	•									•			KN, KC, C,	COMPATIBLE WITH			
	Z2K955WDA	Two Zone Kit									Τ	Zoni			S	V	WW160W				5 Wir	e		24V										
ES	RZ251W	Secondary Zone Controller - Wireless Remote Sensor										Z955W - T955WH				S	អា R250S			Wired Outdoor Temperature Sensor											T755S			
ACCESSORIES	RZ250W	Wireless Outdoor Sensor	ess Outdoor Sensor										W - T	955V	VH	CESSORIES	R251	Wired Indoor Temperature Sensor												T755S				
CCES	Z260W	Damper Module											2955\			ACCES	T15	0	Sta	Stat Guard Cover											Any Thermostat			
A	ZDA250W	Discharge Air Sensor										Z	2955\	V		A	T119	9	Uni	ivers	al W	all Pl	ate								Any Thermostat			
	W150W	Wireless Repeater									1	Wireless Models					E219	9	Weather Resistant Junction Box											Any Model				

Stages * = 2 Stages for conventional heat - Programming ** = Programming only available from the web app